



**MATERIALS**

The sign base material used for the regulatory signs shown on this sheet may be any of the following, of the minimum thickness noted:

	ONE POST		TWO POSTS	
	3' x 4'	4' x 3'	4' x 5'	8' x 4'
FLAT SHEET ALUMINUM	0.100"	0.125"	0.100"	0.125"
HIGH DENSITY OVERLAID PLYWOOD	5/8"	5/8"	5/8"	5/8"
GALVANIZED FLAT SHEET STEEL	14 Gage	12 Gage	16 Gage	14 Gage

The reflective material shall be white or silver reflective sheeting applied to the backgrounds. The texts may be lettering film, silk screened or hand lettered.

**COLORS**

The regulatory signs shown on this sheet shall have black texts on a reflectorized white or silver background.

**TEXT DESIGN**

Letters, digits, spacings and text dimensions shall conform with the standard alphabets and designs prescribed in the Manual on Uniform Traffic Control Devices prepared by the National Joint Committee on uniform traffic control devices.

**SPECIFICATIONS**

The signs shall meet the standard State specifications for "Traffic Signs", Item 701.

REVISIONS AND CORRECTIONS  
AUG. 12, 1963 - DIMENSIONS REVISED ON KEEP OFF MEDIAN, SPEED LIMIT 65 AND MINIMUM 40 SIGNS.

APPROVED  
MAY 6, 1963

*A. J. Bishop*  
CHIEF ENGINEER

*R. H. Carroll*  
ASSY. CHIEF ENGINEER

*G. W. Lane*  
HIGHWAY ENGINEER

*E. W. Dickson*  
CONSTRUCTION ENGINEER

*A. W. Coleman*  
TRAFFIC ENGINEER

DRAWN A.W.C.  
TRACED R.L.B.

TRAFFIC SIGNS  
REGULATORY SIGNS

