



**PROJECT LOCATIONS—I-91
(TRAVEL LANE ONLY)**

- NB MM 62.35 - 65.50 HARTLAND
- NB MM 66.70 - 68.40 HARTLAND-HARTFORD
- NB MM 105.00 - 108.00 NEWBURY
- NB MM 112.03 - 112.95 RYEGATE
- NB MM 115.50 - 116.00 RYEGATE
- NB MM 116.65 - 117.85 RYEGATE-BARNET

- SB MM 71.05 - 72.00 HARTFORD
- SB MM 76.30 - 76.50 NORWICH

NOTES:

1. THE SINGLE PAVEMENT LIFT WEARING COURSE SHALL BE TYPE IV, ITEM 406.25, AS SHOWN ON THE TYPICALS, UNLESS DIRECTED BY THE RESIDENT ENGINEER. ALL LIQUID ASPHALT USED FOR BITUMINOUS CONCRETE PAVEMENT SHALL BE PG 58-34.
2. EMULSIFIED ASPHALT SHALL BE APPLIED ON ALL COLD PLANED SURFACES AT THE RATE OF 0.015 GAL./S.Y. OR AS DIRECTED BY THE RESIDENT ENGINEER.
3. BITUMINOUS CONCRETE PAVEMENT TOLERANCE = 1/4" +/- (TOTAL THICKNESS).
4. COLD PLANING SHALL BE COMPLETED ACCORDING TO TYPICAL OR AS DIRECTED BY THE RESIDENT ENGINEER.
5. DO NOT COLD-PLANE OR PAVE BRIDGES.

**PROJECT
TYPICAL
SHEET**

PROJECT NAME: STATEWIDE
PROJECT NUMBER: IM RUTF(12)

FILE NAME: /pave/05k270/pk270.dgn
PROJECT LEADER: WOOLAVER
DESIGNED BY: JLR
p05k270+y0li

PLOT DATE: 03-JUN-2013
DRAWN BY: JLR
CHECKED BY: JLR
SHEET 2 OF 7