

ITEM DETAIL SUMMARY SHEET 6

LOCATION			MISCELLANEOUS											REMARKS						
BEGIN MILE MARKER	END MILE MARKER	POS.	616.47	618.10	618.30	619.17	620.75	649.31	653.20	676.10			676.12							
			BIT. CONC. GUTTERS & TRAFF. ISL. TON	PORT. CEM. CONC. SIDEWALK, 5 INCH SY	DET. WARNING SURFACE SF	YEILDING MARKER POSTS EACH	SNOW BARRIER, GALV. LF	GEOTEXTILE UNDER STONE FILL SY	TEMP. EROSION MATTING SY	DELINEATOR W/STEEL POST EACH	TYPE II EACH	TYPE III EACH	REMOVAL OF EXIST. DELINEATOR EACH							
SOUTHBOUND																				
174.986	175.048	LT							25	2			2							
175.182	175.378	LT							25	2			2							
175.495	175.788	LT							7	1			1							
175.783	175.788	RT																		
175.790	175.804	LT							72											
175.796	175.811	RT							80											
175.864	175.945	RT								25	1		1							
175.870	175.936	LT								25	1		1							
176.100	176.152	LT								25	2		2							
176.108	176.160	RT								25	2		2							
176.520	176.908	LT								25	2		2							
177.245	177.263	RT									1		1							
177.253	177.268	LT								25	1		1							
EXIT 27 RAMP A																				
0.000	0.210						3			26	7	8	41							
0.008		RT	0.8																	CONSTRUCT BITUMINOUS CONCRETE GUTTER - SEE THE MISCELLANEOUS DETAIL SHEET
0.038		RT	1.1																	CONSTRUCT BITUMINOUS CONCRETE GUTTER - SEE THE MISCELLANEOUS DETAIL SHEET
0.085		RT	1.3																	CONSTRUCT BITUMINOUS CONCRETE GUTTER - SEE THE MISCELLANEOUS DETAIL SHEET
0.134		RT	1.3																	CONSTRUCT BITUMINOUS CONCRETE GUTTER - SEE THE MISCELLANEOUS DETAIL SHEET
EXIT 27 RAMP B																				
0.018	0.281						3			34	10		44							
0.164		LT	0.8																	CONSTRUCT BITUMINOUS CONCRETE GUTTER - SEE THE MISCELLANEOUS DETAIL SHEET
0.225	0.266	RT								25	2		2							INSTALL MTS FLARED AT MM 0.225. INSTALL ANCHOR AT MM 0.266. INSTALL 25.0 LF OF S. B. GUARD RAIL AT MM 0.232 AND 25.0 LF AT MM 0.261.
EXIT 27 RAMP C																				
0.000	0.193						1			6	6	12	24							
0.027	0.068	RT								25	2		2							INSTALL MTS FLARED AT MM 0.027. INSTALL ANCHOR AT MM 0.068. INSTALL 25.0 LF OF S. B. GUARD RAIL AT MM 0.034 AND 25.0 LF AT MM 0.063.
0.030	0.070	LT								25	2		2							INSTALL MTS FLARED AT MM 0.030. INSTALL ANCHOR AT MM 0.070. INSTALL 25.0 LF OF S. B. GUARD RAIL AT MM 0.037 AND 25.0 LF AT MM 0.066.
0.086	0.179	RT								25	1		1							INSTALL MTS FLARED AT MM 0.086. INSTALL 25.0 LF OF S. B. GUARDRAIL AT MM 0.093.
0.086	0.166	LT								25	1		1							INSTALL MTS FLARED AT MM 0.086. INSTALL 25.0 LF OF S. B. GUARDRAIL AT MM 0.093.
SHEET SUBTOTALS:			5.3			7	152	7	325	89	23	20	132							

ITEM DETAIL SUMMARY SHEET #6	PROJECT NAME: DERBY	PLOT DATE: 07-SEP-2011 10:22
	PROJECT NUMBER: IM 091-3(46)	
	FILE NAME: p06a200.dgn	DRAWN BY: STANTEC
	DESIGNED BY: STANTEC	CHECKED BY: JLL
IPARM FILE: p06a200ids06.i		SHEET 14 OF 63