



- * - ADJUST LENGTH OF TAPER AS NECESSARY TO AVOID REMOVING THE MILLED RUMBLE STRIPS.
- ** - REDUCE DIMENSION TO 12'-6" AS NECESSARY TO AVOID REMOVING THE MILLED RUMBLE STRIP.

- COLD PLANE - 1 1/4"
- COLD PLANE - 2 1/2"
- PAVEMENT REMOVAL

- TO THE TOP OF THE CONCRETE BRIDGE DECK OR APPROACH SLAB AND REMOVE THE BARRIER MEMBRANE. REMOVAL OF THE BIT. CONC. PAV'T. WILL BE PAID FOR UNDER ITEM 529.10. REMOVAL OF THE BARRIER MEMBRANE WILL BE PAID FOR UNDER ITEM 580.16.

BITUMINOUS CONCRETE REMOVAL PLAN

NOT TO SCALE

BRIDGE NO.	A (FT)	B (FT)
4IN	60.0	60.0
4IS	60.0	60.0
4IC	60.0	60.0
42N	100.0	60.0
42S	100.0	100.0
43S	100.0	100.0
44N	120.0	120.0
44S	120.0	120.0
15N	100.0	100.0
15S	100.0	100.0

PROJECT NAME: HARTFORD - SHARON
 PROJECT NUMBER: IM MEMB (15)

FILE NAME: ...08 bit conc removal plan.dgn PLOT DATE: 7/29/2009
 PROJECT LEADER: G. BOGUE DRAWN BY: E. ALLING
 DESIGNED BY: M. CHENETTE CHECKED BY: M. CHENETTE
BITUMINOUS CONCRETE REMOVAL PLAN SHEET 9 OF 47

