



NOTES:

1. REINFORCEMENT ABOVE FOOTINGS SHALL BE EPOXY COATED. REINFORCEMENT IN FOOTING SHALL BE UNCOATED. REINFORCEMENT PLACED IN FOOTING AND EXTENDING ABOVE TOP OF FOOTING SHALL BE EPOXY COATED. REINFORCEMENT IN AND INTO F-SHAPE BARRIER SHALL BE SOLID STAINLESS.
2. FOR F-SHAPE BARRIER REINFORCING DETAILS, SEE ABUTMENT DETAILS - SHEET 2.
3. FOR SECTION A-A & SECTION B-B PILASTER REINFORCING DETAILS, SEE ABUTMENT DETAILS - SHEET 3.
4. FOR TYPICAL WINGWALL SECTION REINFORCEMENT, SEE ABUT. 4 WINGWALL REINFORCEMENT - 1.
5. FOR SECTION D-D AND SECTION E-E, SEE ABUTMENT 3 WINGWALL REINFORCEMENT SHEET.

WINGWALL 8 REINFORCEMENT

SCALE 3/8" = 1'-0"

ITEMS USED ON THIS SHEET	
ITEM NO.	DESCRIPTION
501.33	CONCRETE, HIGH PERFORMANCE CLASS A
501.34	CONCRETE, HIGH PERFORMANCE CLASS B
507.15	REINFORCING STEEL
507.17	EPOXY COATED REINFORCING STEEL
900.635	STAINLESS STEEL REINFORCING
900.640	BRIDGE RAILING, F-SHAPE CONCRETE

LEGEND
 NF = NEAR FACE
 FF = FAR FACE
 EF = EACH FACE

PROJECT NAME: WINDSOR	
PROJECT NUMBER: IM 091-1(64)	
FILE NAME: z10o188Abut4RW2.dgn	PLOT DATE: 7/30/2015
PROJECT LEADER: J. WILSON	DRAWN BY: S. GUNN
DESIGNED BY: S. BOYINGTON	CHECKED BY: S. HALLORAN
ABUT. 4 WINGWALL REINFORCEMENT - 2	SHEET 133 OF 156