



ABUTMENT #4, SOUTHBOUND FIRED END, FOOTING IS IN A FILL AREA AND WILL NOT REQUIRE GRANULAR BACKFILL FOR STRUCTURES ITEM. GRANULAR BORROW WILL BE USED COMPLETELY AROUND AND UNDER THE ABUTMENT. SEE SHEET BR503, PLAN & ELEV. VIEW. ABUTMENTS 1,2,3 WILL REQUIRE GRANULAR BACKFILL FOR STRUCTURES, UNDER THE FOOTINGS, EVEN THOUGH PART OF SOME FOOTINGS MAY BE IN FILL AREA.

I-93 BRIDGES 3N&S
 WATERFORD
 IM MEMB(31)
 SHEET 29 OF 48
 FOR REFERENCE ONLY

STATE OF VERMONT	
AGENCY OF TRANSPORTATION	
TOWN OF WATERFORD	Bridge No. B5
HIGHWAY NO. I93	Log Sta.
I93 NB & SB OVER T.H. 12	Surv. Sta. 251+70
APPROACH SLAB DETAILS & ABUTMENT BACKFILL AND EXCAVATION LIMITS TYPICAL	
Designed by FARNSWORTH, S.	Drawn by R. JENSEN
Checked by G. ROGERS date 6/80	Bridge Design Supervisor F. W. Bolcum date 7/80
PROJECT WATERFORD	PROJECT NO. I93-1(3) 1/2
Bridge Sheet No. BR 509	Sheet 130 of 331