



Note: Steel to be A.S.T.M. A36  
 Holes to be 15/16"  
 Paint one shop coat per Vermont Specs.

RECEIVED MAR 28 1966  
 CK'D BY WBT OK'D BY RLD  
 RESUBMIT APPROVED  
 BY HWS DATE 4-5-66  
 IR 089-1(13)  
 This sheet for information only  
**BR 11 N & S**  
 SHEET 100 OF 101

Proj. I-89-1(6)  
**N. B. E.S. BRIDGES**  
 INTERMEDIATE CROSS FRAMES  
 Bancroft & Martin, Inc.  
 South Portland 7, Maine  
 I-89 BRIDGE OVER WHITE RIVER  
 HARTFORD, VERMONT

15/16" Holes are for High Tensile Bolts  
 They are to be placed from girths  
 and girths are to be placed on any  
 surface within 4" of such open  
 holes.

INTERMEDIATE FRAME CF220  
 4 REQ.

Quantities shown are for one bridge.  
 Add suffix N to marks for Northbound Bridge. (Bill of mat'l. S65N)  
 S " " " " Southbound Bridge. (Bill of mat'l. S65S)

DRAWN	2-25-66	TFB	CUSTOMER	CIANCHETTE BROS. INC.
REVISION			DESIGNER	VERMONT DEPT. OF HIGHWAYS
REVISION			ORDER NO.	Verbol
REVISION			DWG. NO.	65-374-565

(5)