



NOTES
 WITH THE EXCEPTION OF COLUMNS
 CHAMFER FOR ALL EDGES TO BE 3/4"
 DESIGN BEARING = 8 KIPS PER
 SQ. FT. OR AS MODIFIED BY AASHTO
 SPECIFICATIONS (1959).

THE USE OF SHEET METAL CONES IS
 OPTIONAL. ANY OTHER MEANS OF
 PLACING ANCHOR BOLTS MAY BE
 USED ON APPROVAL OF THE ENGINEER
 IN THE FIELD.

SHEET METAL CONE
 3" = 1'-0"
 QUANTITIES (ONE BRIDGE ONLY)

NO.	ITEM	NET	OVER-	TOTAL	FINAL
107	STRUCTURE ENG.	172.04	12.64	184.68	176
40-B	CONCRETE CLASS "B"	187.04	9.04	196.08	188
402	REINFORCING STEEL (SEE REINFORCING SHEET)	163.34	-	163.34	14

IM 091-1(33)
 This sheet for information only
BR 3 N&S
 Sheet 107 of 114

CAUTION:
 REPRODUCTION
 IS NOT TO SCALE

STATE OF VERMONT
 DEPARTMENT OF HIGHWAYS

TOWN OF GUILFORD
 ROUTE NO. INTERSTATE LOG STA.
DETAILS OF PIER #2
 @ STATION 327+44
 SCALE AS SHOWN
 SURVEYED BY POGAR
 DRAWN BY RLB CHECKED BY HES
 PROJECT NO. I-001-1(6)
 SHEET 107 OF 114