



CONSTRUCT DRIVES

| LT       | RT     | LT     | RT     |
|----------|--------|--------|--------|
| 309+50   | 320+75 | 317+75 | 323+60 |
| 317+20   |        | 317+20 |        |
| 319+22.5 |        | 317+20 |        |

STONE FILL FOR SLOPE PROTECTION  
 322+10 - 323+40 RT.

PLAN  
 DATE  
 BY  
 CHECKED  
 APPROVED

B. S. ...  
 ...  
 ...

- ESTIMATE OF BRIDGE QUANTITIES -

| ITEM  | DESCRIPTION                             | NET   | ORIG | FORM  | FINISH |
|-------|---|-------|------|-------|--------|
| 106-C | UNCLASSIFIED CHANNEL EXCAVATION         | 3364  | 830  | 3700  | 3364   |
| 107   | STRUCTURE EXCAVATION                    | 39    | 99   | 100   | 99     |
| 312   | TAR EMULSION FOR BRIDGE FLOORS          | 172   | 172  | 164   | 164    |
| 363   | BIT CONCRETE FAVORITE FOR BRIDGE FLOORS | 32    | 32   | 37    | 43     |
| 401-B | CONCRETE, CLASS "B"                     | 772   | 10   | 10    | 176    |
| 402   | REINFORCING STEEL                       | 2269  | 1    | 2309  | 2269   |
| 404-A | STRUCTURAL STEEL                        | 10222 | 1    | 10222 | 10222  |
| 407   | ASPHALTIC ASBESTOS COATING              | 11    | 1    | 11    | 11     |
| 412   | REMOVAL OF PRESENT SUPERSTRUCTURE       | 1     | 1    | 1     | 1      |
| 501   | TREATED TIMBER PILING                   | 14    | 1    | 1     | 1      |
| 502   | STONE FILL FOR SLOPE PROTECTION         | 1050  | 1050 | 1050  | 1050   |
| 521   | STONE FILL (HEAVY TYPE)                 | 434   | 434  | 435   | 435    |
| 522   | STONE FILL FOR SLOPE PROTECTION         | 294   | 29   | 320   | 343    |
| 523   | TWO CABLE GUARD RAIL                    | 168   | 168  | 168   | 168    |

- LIST OF BRIDGE SHEETS -
- 1 PLAN & PROFILE
  - 2 DETAILS OF ABUTMENTS 1 & 2
  - 3 REINFORCING STEEL DETAILS
  - 4 STD DWG 312-25(1-20) MODIFIED - 84' SPAN
  - 5 " " 32-20-1 (TWO CABLE GUARD RAIL)
  - 6 " " 32-20-26 (DETA B, C, D, F OR G)
  - 7 " " 35-56-2 (SHEARKEYS STANDS & LIGHTS)
  - 8-9 CHANNEL SECTIONS

