



GUARD RAIL, HEAVY DUTY STEEL BEAM
 W/ WOOD POSTS, TYPE II
 110+53 ~ 110+84 Lt.
 110+52 ~ 111+00 Rt.
 111+65 ~ 111+88 Lt.
 111+63 ~ 111+82 Rt.

Rev. Curve Data
 Δ = 32°-49'-19" Lt.
 D = 18°-00'-00"
 R = 318.31
 T = 93.75
 L = 182.34
 E = 13.52
 2T-L = 5.16
 Banking 0.060

Curve Data US Pts #9
 Δ = 47°-45'-54" Lt.
 D = 28°-00"
 R = 209.63
 T = 137.92
 L = 242.02
 E = 10.93
 2T-L = 33.82

BEGIN R.O.W. PROJECT
 STA. 109+88 52' RT.

END R.O.W. PROJECT
 STA. REV. 113+35 CL.

DATUM
 VERTICAL NGVD 73
 HORIZONTAL _____

Drive Curve (Calc)
 Δ = 30°-00'-00"
 D = 114°-35'-30"
 R = 50.00'
 T = 13.40'
 L = 26.18'
 E = 1.76'
 2T-L = 0.62'
 PC = 100.00 = Ch Line 9+21.79 (1' Lt.)
 PT = 26.18

MAY 28 1996

SURVEYED BY	DATE
DRAWN BY	DATE
TRACED BY	DATE
PROJ. BURKE No. BRS 0287 (3)S	
SHEET 5 OF 5	