



Rev Curve 2
 Δ 35° 56' 30" Rt
 D 7' 30"
 T 763.94'
 L 247.44'
 E 479.22'
 Brk 0.030 ft/ft

Curve 2
 Δ 26° 08' 30" Rt
 D 14' 30"
 T 763.94'
 L 247.44'
 E 479.22'
 Brk 0.030 ft/ft

Rev Curve 1
 Δ 3° 37' 01" Lt
 D 2' 00"
 T 2864.79'
 L 90.45'
 E 180.65'
 Brk 1.43
 0.030 ft/ft

Revision History
 Revision 1
 Rev 15+33 Rt (20' wide)
 Rev 16+70 Rt
 Rev 14+13 Lt (match existing)
 Rev 18+00 Rt
 Rev 18+30 Lt

General Note:
 Drives are to be constructed with a minimum width of 14' and a flare radius of at least 20' or as directed by the Engineer.

DATUM
 VERTICAL Assumed
 HORIZONTAL N/A

APR 1 1987

Scale 1" = 40'

SURVEYED BY: _____ DATE: _____
 DRAWN BY: _____ DATE: _____
 TRACED BY: _____ DATE: _____

FAIRFAX
 PROJ BRS NO 0229 (2)
 SHEET 6 OF 10