



* BITUMINOUS CONCRETE CURB
ITEM 535 TYPE II
SB 639+00 - 641+00 Lt.

STONE FILL FOR SLOPE
PROTECTION ITEM 512
NB 642+00 - 642+50 Rt.

* STAGE II CONSTRUCTION

* THREE CABLE GUARD RAIL/
LIGHT STEEL POSTS, ITEM 538
NB 639+00 - 644+50 Lt.

DRILLING AND BLASTING SURVEY
OF SOLID ROCK SUBGRADE
ITEM 110
NB 641+25 - 649+50
SD 641+25 - 649+00 - 641+57

DRILLING & FRESH SETTING OF
SOLID ROCK, ITEM 125
647+25 - 649+75
NB 647+64 - 649+00
SB 647+64 - 649+00

PLAN
 DATE
 DRAWN BY
 CHECKED BY
 APPROVED BY

Δ 6°00'00" DI
 D 07'20"
 R 11259.16'
 T 60°30'
 L 1600.00'
 E 27.96'
 Sbk. 27.77 (0211)

STATION	LOCATION	OFFSET	DESCRIPTION
643+00	RT.	100'	Concrete
643+50	LT.	233'	Drilled Hole

STONE FILL FOR SLOPE
 PROTECTION, ITEM 512.
 NB 639+00 - 639+25 Rt.
 NB 640+00 - 641+75 Rt.
 NB 641+75 - 642+75 Rt.
 NB 642+75 - 643+75 Rt.
 NB 644+50 - 645+50 Rt.
 NB 646+25 - 647+25 Rt.
 SB 647+00 - 647+25 Lt.

STANDARD STEEL BEAM GUARD RAIL
 ITEM 545-A
 NB 641+55 - 642+50 Rt.

PROPERTY LINE FENCE, ITEM 503-I MOD
 SB 639+00 - 649+00 Lt.
 NB 639+00 - 649+00 Rt.

STANDARD STEEL BEAM GUARD RAIL
 ITEM 545-A
 NB 641+55 - 642+50 Rt.

CONTROL OF ACCESS IS
COMPLETE ON THIS SHEET

HARTFORD - SHADON

DEC 19 1973

Sheet 15