

Begin Drilling & Blasting of Solid Rock Subgrade
 NB 5206+00 - 5216+00
 SB 5206+00 - 5216+00

Curve Data
 NB 1 J.B.
 A = 65° 55' 15"
 Q = 2107.30'
 L = 350'
 T = 1238.77'
 E = 317.94'
 LT = 233.48'
 JT = 116.80'
 Δ = 33° 56' 12"
 L = 1533.96'
 E = 1637.02'
 B.M. = 196.77'

Property Line Fence
 w/ Steel Posts
 SB 5205+00 - 5216+00

Demolition & Disposal of Buildings
 NB 5207+00 R. (MS)

Chain Link Fence
 NB 5206+00 - 5216+00
 SB 5205+00 - 5216+00
 To be erected prior to construction


Sub-Mapping
 NB 5206+00 - 5216+00
 SB 5205+00 - 5216+00
 NB 5208+00 - 5211+00
 NB 5204+00 - 5207+00

Topsoil Stockpiles
 NB 5212+00 - 5214+00 E. (3000 cu)

POOR ORIGINAL COPY

GUARD RAIL, STD. STEEL BEAM w/ STEEL POSTS - TYPE II
 NB 5215+00 - 5216+00 RT. (6'-3" SPACING)
 NB 5216+00 - 5216+00 LT.

Control of Access
 Complete on this sheet



STATE of VERMONT DEPARTMENT of HIGHWAYS	
BRADFORD	
McFARLAND-JOHNSON CONSULTING ENGINEERS	
DESIGNED BY: T.S. FRANCY: L.F.	CHECKED BY: JAW DATE: 6-1-62
PROJECT No: 1-912(61)	SHEET 24 OF 130
CONTRACT No: (26)	78 930