



CABLE GUARD RAIL REQUIRED

STATIONS	LENG.	CONSTANT	PAV. LENGTH
73+00-73+40	40'	84°	84'
73+40-73+80	40'	84°	84'
73+80-74+20	40'	84°	84'

CULVERT REPAIRS REQUIRED

STATION	DIAM.	LENG.	REPAIRS
73+00	16"	12'	1.5 cy.
81+25	18"	12'	1.5 cy.
83+57	18"	12'	1.5 cy.
85+10	18"	12'	1.5 cy.

WOODGUIDE POSTS

STATION	LEFT	RIGHT
73+04	24'	24'
83+77	24'	24'
85+10	24'	24'

ENTIRENESS MACADAM GUTTER REQUIRED

STATIONS	LENG.	REQUIREMENTS
78+00-81+25	325'	10' width
81+25-82+50	125'	10' width
82+50-83+57	107'	10' width
83+57-85+10	223'	10' width

COOP. GALV. METAL PIPE

STATION	LENG.	DIAM.	DEPTH	REQUIREMENTS
76+30-77+30	100'	36"	2.7 ft.	2.7 ft.

GRADED COBBLE GUTTER REQUIRED

STATIONS	LENG.	WIDTH	AREA
71+30-76+30	500'	3'6"	894 sq. ft.
75+33-76+30	113'	3'6"	443 sq. ft.

500 B.M. #10 TOP OF LEDGE 25' LT. STA 75+12 ELEV. 534.36
 B.M. #10A TOP OF LEDGE 48' LT. " 75+50 " 534.62
 B.M. #11A TOP OF DOULDER 125' RT. " 77+50 ELEV. 503.25

SERIES F 1110-26
 SHEET 9 of 51