


RAMP H CURVE DATA

| | |
|----|---------------|
| Δ | 10°46'-35" RT |
| CD | 4'-05'-33" |
| R | 1400.00' |
| T | 132.05' |
| L | 243.32' |
| E | 6.21' |
| PC | 517+50.81 |
| PT | N 149.34 00 |
| PI | E 310.00475 |

*** JUTE MATTING - ITEM 623**
 Sta 517+50 to 528+50, N.B. RT
 Sta 513+50 to 528+50, Median
 Sta 521+50 to 528+50, S.B. LT
 Sta 513+50 to 514+00, N.B. RT
 Ramp H Sta 10+00 to 14+50, LT

DRILLING AND BLASTING OF SOLID ROCK
 SUBGRADE-ITEM 115
 Sta 523+40-528+50, S.B.
 Sta 523+25-528+50, N.B.

STONE FILL FOR SLOPE PROTECTION
 (Light Type) - ITEM 512
 Sta 516+40 to 517+80, N.B. RT
 Sta 516+16 to 521+25, S.B. LT
 Sta 514+00, S.B. LT
 Sta 517+50, N.B. RT
 Sta 517+50, S.B. LT
 Ramp H Sta 10+00 to 14+50, RT
 Ramp G Sta 31+00 to 33+82, RT



BENNINGTON
 F 019-1(6)
 PLAN STA 513+50 TO 528+50

| | | |
|----------------|---------------|------------------------------------------|
| Sheet 27 of 67 | DATE 11/14/69 | GOODKIND & O'DEA CONSULTING ENGINEERS |
|----------------|---------------|------------------------------------------|

Checked by: S.J.P.
 Drawn by: M.S.L.
 Prepared by: S.J.P.