



CONSTRUCT APPROACH
LI
170+00

DRILLING AND BLASTING OF
SOLID ROCK SUBGRADE
176+50 - 178+00
2-2

CONSTRUCT DRIVE
LI
176+21 176+00
170+00 (Approach Sta 4+70 LI)

BM #22 ✓
S.I.R. 30' LOCUST
Assmd. El. 57.21

BM #22 B.
S.I.R. 40' loc.
Assmd. El. 58.50

STONE FILL FOR SLOPE PROTECTION (LIGHT TYPE)
Approach Sta. 2+25 - 4+75 LI
+55

TWO CABLE GUARD RAIL
LI
Approach Sta. 1+73 - 4+77
1-65 3-27
CONSTRUCT SPECIAL DITCH TO BE PAID FOR
UNDER THE ITEM OF COMMON EXCAVATION
RI
166+00 - 170+21.5

J. DERMODY
Wood Guide Post
LI
Pegs Sta. 1+45, 1+53, 2+92, 4+02
5 Guide Post in Runouts Side Sta. 2+43
Maintain 170+00

ML POST Sta 170+00
Approach Sta. 0+00

BM #22A
36" E
Assmd. El. 43.17

BM 21-A
317 6" B
Assmd. El. 57.15

m.e.a.d.o.w
175+72 61 RT
12' x 12' Stone 12' from 175+72
176+00 RI
New 15" 33' Pipe (CGMP) 6' from
CGMP 16' (25%)
176+30
Δ 87° 18' 30" RI
D 12'
R 477.5 New 6" 48' Underdrain
@ 60' RI, 60' Elbow LI
T 435.6
L 727.6
E 182.5
Bank 1" per ft.

