FED. AID
105-E 1936 5 24

790+00 — 797+00 Lt.
DITCH SLOPE TO BE SEEDED
(ITEM "90-C)

797+00 — 799+00 Lt.
CLEARING & TRIMMING ROADSIDE
TREES TO BE PRUNED & THINNED OUT FOR VISION
(ITEM #92-B)

REV. P.I. 785+50.4 = 785+49.4
SUR. P.I. 785+53.2 = 785+46.5, Δ 32°-48', D 14°
REV. LINE, PARALLEL TO SUR. LINE AFT LT.
R.O.W. LIMITS
NEW ENGLAND POWER ENGINEERING AND SERVICE CORP.
#19; #1 Wilmington
N.E. POWER Co.
Wilmington Savings Bank
#16
Construct Parking Area STA 791+30 - 792+30 LT.
REV. P.I. 792+79.6 = 792+79.3, 65°41' Rt., D 2°30'
SUR. P.T. 792+82.2 = 792+81.0, Δ 13°22', D 6°
Pasture
Woods
#14
#15
Revised ℄
N.E. POWER Co.
DEERFIELD RIVER
BM #109 16" Y. BIRCH EL. 1577.78
SUR. P.T. 788+12.7 = 788+10.2, Δ 18°36', D 7°
REV. CURVE Δ 20°42' RT. D 7°30' R 764.5 T 139.5 L 276.0 E 12.6
REV. P.C. 786+10.6
REV. P.T. 786+86.9 = 786+85.0 Eq. 1.9 Ft.
Δ 21°16' D 7° P.T. 797+12.6 = 797+08.8
BM #110 16" Y. BIRCH EL. 1598.62

NOTE
STA 793+25 TO 798+00 RT.
Boulders & Rock from Roadway Excavation to be used for the Protection Side Fills as shown on the Cross Sections.
Any Excess Rock is to be used in the Construction of Embankments.

PARCEL	KIND OF INSTRUMENT	DATE OF INSTRUMENT	GRANTOR	GRANTEE	RECORDED IN BOOK	RECORDED IN PAGE	RECORDED DATE	REMARKS
#16 A-B-C-D	W.D.	6-29-35	WILMINGTON SAVINGS BANK	ST. OF VT.	8	345-6-7	8-10-35	

Revised Grade of May 1936
+1.380%
-5.197%
-1.970%
-0.968%
Revised 9-22-38
-0.865%
790+25 300' V.C. 1571.00
Revised (May '36) 792+75 200' V.C. 1566.08
793+75 300' V.C. 1560.20
787+25 300' V.C. 1586.59
Sta. 786 786+85.0 Rev. P.T. 786+86.9
783+00-783+75 SHAPING COURSE OF GRAVEL
783+75-799+00 12" SUB-BASE OF GRAVEL

BM #109 SPIKE IN TRUNK OF 12" Y. BIRCH 25' RT. OF STA. 787+41 ELEV. 1577.78
BM #110 " " ROOT " 8" ASH 14' RT. " " 797+87 " 1598.62

SECTION FARMINGTON
SHEET 24

4