



**SECTION R-2**  
SUMMARY OF QUANTITIES  
Item 10-11 Common Excavation including Borrow 1670 Cu Yds.  
20A Gravel Surface Course 350 " "  
67 Cable Guard Rail 400 Lin. Ft.

**SECTION R-2**  
SHEETS TO BE USED  
2 SHEETS PLAN AND PROFILE  
2 CROSS SECTIONS  
EARTHWORK SHEET  
TYPICAL SECTION OF IMPROVEMENT 24" GRAVEL  
S-22 STANDARD STRUCTURES

**SECTION B-5**  
SUMMARY OF QUANTITIES  
Item 10-11 Common Excavation including Borrow 280 Cu Yds.  
15 Structure Excavation 638 " "  
20A Gravel Surface Course 160 " "  
34A Concrete Class 9(1-2-4) 353 " "  
34B " 3(1-2 1/2-5) 288 " "  
35 Reinforcing Steel 11,340 Lbs.  
67 Cable Guard Rail 340 Lin. Ft.  
Maintaining Traffic and removing present Superstructure and Piers Lump Sum  
1390 Cu Yds. of Borrow from Section R-1

**SECTION B-5**  
SHEETS TO BE USED  
2 SHEETS PLAN AND PROFILE  
2 CROSS SECTIONS  
EARTHWORK SHEET  
TYPICAL SECTION OF IMPROVEMENT 24" GRAVEL  
S.T.B. 20x60 30 SPAN TEE BEAM WITH GRAVEL  
S.A. 3 SKEW ENDS 30"  
S.D. 2 TYPICAL DETAILS  
S.O. 2A  
S.A. 5 CABLE GUARD RAIL AND CURB  
S.A. 6 30" SKEW 14' ABUTMENT  
S-22 STANDARD STRUCTURES

