



STATION	ELEVATION
477	1911.6
478	1906.23
479	1904.9
480	1902.53
481	1900.2
482	1900.43
483	1897.93
484	1895.8
485	1895.4
486	1895.29
487	1893.3
488	1893.09
489	1893.2
490	1893.2
491	1892.6
492	1892.14
493	1886.8
494	1886.8
495	1886.74
496	1884.4
497	1884.12
498	1885.9
499	1893.26
500	1884.2
501	1892.16
502	1882.2
503	1890.97
504	1888.5
505	1889.22
506	1888.13
507	1890.3
508	1887.39
509	1887.7
510	1885.32
511	1888.7
512	1883.60
513	1880.8
514	1880.43
515	1874.2
516	1877.63
517	1871.6
518	1874.58
519	1866.2
520	1871.32
521	1861.6
522	1868.93
523	1869.3
524	1864.74
525	1861.45
526	1855.9
527	1853.26
528	1853.3
529	1853.2
530	1853.2
531	1849.9
532	1853.26
533	1853.26
534	1849.9

B.M. 76 SPIKE IN ROOT 18" PINE 142' RT STA 479+76 ELEV 1906.50
 B.M. 77 SPOT ON BOULDER 145' RT STA 483+95 ELEV 1895.69
 B.M. 78 S.I.R. 18" SPIKE 12' RT STA 488+94 ELEV 1892.71

THIS SHEET
 Revised 3 July 46
 W.F.S.

STATE OF MASSACHUSETTS
 91(8) 1946 8 59

TYPICAL SECTION FOR OUTLET DITCHES
 STA 482+54.1 LT - 487+38.1 LT + STA 483+49.1 LT FAP 93(8)

Winhall F. S. 3(2)
 sheet 8 of 53