

TEMPORARY 4in YELLOW LINE (PAINT)
DURABLE 4in YELLOW LINE (THERMOPLASTIC)
STA 270+00 TO 300+00 SOLID LT&RT

TEMPORARY 4in WHITE LINE (PAINT)
DURABLE 4in WHITE LINE (THERMOPLASTIC)
STA 270+00 TO 300+00 SOLID LT&RT

STA 276+10 TO 280+35 LT
REMOVAL AND DISPOSAL
OF GUARD RAIL

STA 276+47 TO 279+98 LT
INSTALL STEEL BEAM
GUARD RAIL, GALVANIZED

STA 276+10 TO 276+47 LT
INSTALL MANUFACTURED
TERMINAL SECTION, FLARED

STA 279+98 TO 280+35 LT
INSTALL MANUFACTURED
TERMINAL SECTION, FLARED

STA 270+00 TO 270+95 RT
REMOVAL AND DISPOSAL
OF GUARD RAIL

STA 270+00 TO 270+58 RT
INSTALL STEEL BEAM
GUARD RAIL, GALVANIZED

STA 270+58 TO 270+95 RT
INSTALL MANUFACTURED
TERMINAL SECTION, FLARED

TO MAIDSTONE
MATCH LINE - SEE PREVIOUS SHEET
15ft
15ft
15ft

274+95 LT
BEGIN MTS, FLARED
& NEW SBGR

272+42.5 RT
BEGIN MTS, FLARED
& NEW SBGR

269+92.5 RT
END MTS, FLARED
& NEW SBGR

BRIDGE #7
STA 276+60= MM 5.24
LEVEL & PAVE w/1/4"

279+32.5 LT
END MTS, FLARED
& NEW SBGR

275+92.5 RT
END MTS, FLARED
& NEW SBGR

STA 273+45 TO 276+95 RT
REMOVAL AND DISPOSAL
OF GUARD RAIL

STA 273+82 TO 276+58 RT
INSTALL STEEL BEAM
GUARD RAIL, GALVANIZED

STA 273+45 TO 273+82 RT
INSTALL MANUFACTURED
TERMINAL SECTION, FLARED

STA 276+58 TO 276+95 RT
INSTALL MANUFACTURED
TERMINAL SECTION, FLARED

STA 296+50 TO 300+00 LT
REMOVAL AND DISPOSAL
OF GUARD RAIL

STA 296+50 TO 296+87 LT
INSTALL MANUFACTURED
TERMINAL SECTION, FLARED

STA 296+87 TO 300+00 LT
INSTALL STEEL BEAM
GUARD RAIL, GALVANIZED
w/8 FT POSTS

TO MAIDSTONE
MATCH LINE - SEE ABOVE
18" CSP
18" CSP

295+43.5 LT
BEGIN MTS, FLARED
& NEW SBGR

295+32.5 RT
BEGIN MTS, FLARED
& NEW SBGR

298+45 RT
END MTS, FLARED
& NEW SBGR

REMOVAL AND DISPOSAL OF GUARD RAIL
STA 270+00 TO 270+95 RT
STA 273+45 TO 276+95 RT
STA 276+10 TO 280+35 LT
STA 296+32 TO 299+70 RT
STA 296+50 TO 300+00 LT

STEEL BEAM GUARD RAIL, GALVANIZED
STA 270+00 TO 270+58 RT
STA 273+82 TO 276+58 RT
STA 276+47 TO 279+98 LT

MANUFACTURED TERMINAL SECTION, FLARED
STA 270+58 TO 270+95 RT
STA 273+45 TO 273+82 RT
STA 276+10 TO 276+47 LT
STA 276+58 TO 276+95 RT
STA 279+98 TO 280+35 LT
STA 296+32 TO 296+69 RT
STA 296+50 TO 296+87 LT
STA 299+33 TO 299+70 RT

STEEL BEAM GUARD RAIL, GALVANIZED w/8 FT POSTS
STA 296+69 TO 299+33 RT
STA 296+87 TO 300+00 LT
DITCHING LOCATIONS (REFER TO SHEET 10 FOR DETAILS)
STA 270+00 TO 273+40 LT

- LEGEND
- N = NEW
 - R = REMOVE
 - R&S = REMOVE & SALVAGE
 - S = SALVAGE
 - RET = RETAIN
 - B-TO-B = BACK TO BACK
 - ⊕ □ = CATCH BASIN/DI (N.W.) = NO WORK REQUIRED (TYP. FOR D.I.'S, & C.B.'S WHERE NOTED)
 - I = YIELDING MARKER POST
 - ⊗ = UTILITY POLE
 - = DRIVE

PAVING PROJECT LAYOUT SHEET #19

DESIGNED BY	BCE/PJM	DATE	10-06
DRAWN BY	C.E.A., INC.	DATE	10-06
DESIGN FILE NO.	06c042.dgn		
PRF FILE	06c042p19.I	DATE PLOTTED	24-AUG-2009
PROJ. NAME	MAIDSTONE - BLOOMFIELD		
PROJ. NO.	STP 2609(1)S		
SHEET	29	OF	40 SHEETS