

Bituminous Concrete Material, Drives

Station	Offset	Length	Width	SF	SY (SF / 9)	Date Completed
103+52	LT	28	10	280.00	31.11 ✓	11/15/2010
104+80	LT	13	10	130.00	14.44 ✓	11/10/2010
104+88	RT	13	6.5	84.50	9.39 ✓	11/9/2010
		24	14	336.00	37.33 ✓	11/9/2010
		18	6.5	117.00	13.00 ✓	11/9/2010
105+11	LT	12	10	120.00	13.33 ✓	11/10/2010
105+11	LT	3.5	16.5	57.75	6.42 ✓	11/10/2010
105+63	RT	17	14	238.00	26.44 ✓	11/12/2010
		6	6.5	39.00	4.33 ✓	11/12/2010
105+90	RT	20.5	13.5	276.75	30.75 ✓	11/9/2010
106+86	LT	12.5	10	125.00	13.89 ✓	11/10/2010
107+71	RT	14	13	182.00	20.22 ✓	11/12/2010
108+20	LT	41.5	10	415.00	46.11 ✓	11/15/2010
108+63	RT	33.5	11	368.50	40.94 ✓	11/12/2010
109+51	RT	30	11.5	345.00	38.33 ✓	11/12/2010
111+61	RT	21.5	10	215.00	23.89 ✓	11/12/2010
112+52	RT	16.5	8.5	140.25	15.58 ✓	11/12/2010
113+43	LT	37	12.5	462.50	51.39 ✓	11/12/2010
		95	11.5	1092.50	121.39 ✓	11/15/2010
113+84	RT	21.5	6.5	139.75	15.53 ✓	11/12/2010
114+43	LT	21.5	13	279.50	31.06 ✓	11/12/2010
114+65	RT	20.5	5	102.50	11.39 ✓	11/12/2010
114+79	LT	34	13	442.00	49.11 ✓	11/12/2010
		8.5	2.5	21.25	2.36 ✓	11/12/2010
115+64	RT	22.5	4.5	101.25	11.25 ✓	11/12/2010
116+31	LT	19.5	12.5	243.75	27.08 ✓	11/12/2010
117+31	LT	16.5	11.5	189.75	21.08 ✓	11/12/2010
122+26	LT	61	3.5	213.50	23.72 ✓	11/12/2010
122+76	LT	32	4	128.00	14.22 ✓	11/12/2010
126+64	RT	13	17	221.00	24.56 ✓	11/15/2010
		12.5	7	87.50	9.72 ✓	11/15/2010
129+60	RT	21	2	42.00	4.67 ✓	11/12/2010
130+55	RT	22	2	44.00	4.89 ✓	11/12/2010
131+96	LT	19	4.5	85.50	9.50 ✓	11/12/2010
132+22	RT	25.5	3	76.50	8.50 ✓	11/12/2010
132+62	LT	46	6.5	299.00	33.22 ✓	11/12/2010
133+05	RT	17.5	3.5	61.25	6.81 ✓	11/12/2010
146+30	RT	37	5	185.00	20.56 ✓	11/2/2010
158+06	LT	18.5	4	74.00	8.22 ✓	11/2/2010
173+45	RT	31	4.5	139.50	15.50 ✓	11/2/2010
178+42	RT	86	4	344.00	38.22 ✓	11/2/2010

Page 2 Total = 949.47 SY ✓

Page 1 + Page 2 = Final Total: 1007.72 + 949.47 = 1957.19 SY ✓