

STATE OF VERMONT
AGENCY OF TRANSPORTATION

ITEM DETAIL SUMMARY SHEET 3

BEGIN STATION	END STATION	POS.	201.31 THINNING/ TRIMMING FOR SIGNS	203.30 EARTH BORROW	402.13 AGG. SHOULD. RAP	525.10 REMOVAL OF EXIST. RAILING	525.55 BRIDGE RAILING REPAIR TYPE II	604.412 REHAB. D. I. CLASS I	604.415 REHAB. D. I. CLASS II		616.35 TREATED TIMBER CURB	616.47 BIT. CONC. GUTTERS AND TRAF. ISLANDS	619.17 YIELDING MARKER POSTS	621.20 STEEL BEAM G. R., GALV.	621.205 STEEL BEAM G. R. GALV. W/8FT POSTS	621.215 H. D. STEEL BEAM G. R. GALV. W/8FT POSTS	621.50 MANUF. TERMINAL SECTION, FLARED	621.60 ANCHOR FOR S. B. G. R.	621.70 G. R. APPRCH SECTION & DISP. GALV. TYPE I	621.80 REMOVE & DISP. OF G. R.	629.20 ADJUST ELEV. VALVE BOX	651.35 TOPSOIL	676.10 DEL IN. WITH STEEL POSTS	676.12 REMOVAL OF EXIST. DEL IN.	REMARKS
			EACH	CY	TON	LF	LF	EACH	EACH		LF	TON	EACH	LF	LF	LF	EACH	LF	EA	LF	EACH	CY	EACH	EACH	
184+16	185+41	RT		25										87.5			1				125	5	1	1	CONNECT TO EXISTING GUARDRAIL AT STA. 184+16 INSTALL FLARED MTS @ STA. 185+03.5
190+32	193+07	RT		50							225			200			2				275	10	2	2	INSTALL FLARED MTS @ STA.190+32 AND STA. 192+69.5
193+54	197+91.5	RT		50							350			400			1				437.5	5	1	1	CONNECT TO EXISTING GUARDRAIL AT STA. 193+54 INSTALL MTS @ STA. 197+54
193+17.5	194+80	LT		50										87.5			2				162.5	10	2	2	INSTALL FLARED MTS @ STA. 193+17.5 AND STA. 194+42.5
195+88.5	198+76	LT		50										212.5			2				287.5	10	2	2	INSTALL FLARED MTS @ STA. 195+88.5 AND STA. 198+38.5
197+77	203+78	RT										31.2													
198+43	204+83	LT										33.2													
248+14	255+78	LT										39.6													
253+70	259+57.5	RT												591.5				2			587.5	10	2	2	INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA.253+70 AND STA. 259+57.5
266+90	269+15	LT									120			177			1	1			225	5	1	1	INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA.266+90
268+02.5	269+21.25	RT												70.75 75				1	1		118.75	5	1	1	INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA.268+02.5
270+79	271+41.5	LT									30			14.5				1	1		62.5	5	1	1	INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA.271+41.5
270+90	271+52.5	RT												12.5				1	1		50	5	1	1	INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA.271+52.5
282+54.00	363+26.40	LT&RT			162			6	1				18												
289+15	289+22	LT																							REMOVE SIDEWALK AND RECONSTRUCT SIDEWALK RAMP TYPE I, EXAMPLE 1 FROM STANDARD DRAWING C-3A. SEE TABLE ON MISCELLANEOUS DETAIL SHEET FOR ITEMS AND QUANTITIES
SUBTOTAL THIS SHEET			-	225	162	-	-	6	1		725	104	18	991.5	862.25 866.5	-	8	6	4	2331.25	-	70	14	14	
SUBTOTAL SHEET 15			1	575	1625	-	-	12	3		-	-	98	2102	3656	200	23-24	6	-	6550	4	135	27	27	
SUBTOTAL SHEET 16			-	575	-	175	175	-	-		-	-	-	4031	4943.5 4941	130	23-22	6	-	9825	-	145	29	29	
ROUNDING				-	13	-	-	-	-		-	1	-	0.5	38.25	-	-	-	-	18.75	-	-	-	-	
TOTAL			1	1375	1800	175	175	18	4		725	105	116	7125	9500 9501.75	130	54	18	4	18725	4	350	70	70	

ITEM DETAIL SUMMARY SHEET 3	PROJECT NAME: CAMBRIDGE-FAIRFAX
	PROJECT NUMBER: STP 2713(I)
	FILE NAME: p07B182.dgn
	PLOT DATE: 29-DEC-2014 13:46
	PROJECT LEADER: CDL
	DRAWN BY: SJL
	DESIGNED BY: SJL
	CHECKED BY: EPD
	PLOT FILE: p07B182_17.i
	SHEET 17 OF 36