



**DITCHING NOTES**

1. PIPE INLET AND OUTLET AREAS, AND DITCH CLEANING THROUGHOUT THE PROJECT, SHALL BE PERFORMED AT LOCATIONS IDENTIFIED ON SHEET 22 AND AS DIRECTED BY THE ENGINEER. PAYMENT WILL BE UNDER THE APPLICABLE EQUIPMENT RENTAL ITEM(S).
2. GRADES BETWEEN AND INCLUDING 0 AND 2.5 PERCENT SHALL USE ITEM 651.25, HAY MULCH OR ITEM 653.20, TEMPORARY EROSION MATTING AS DIRECTED BY THE ENGINEER. GRADES OVER 2.5 PERCENT SHALL USE ITEM 649.31, GEOTEXTILE UNDER STONE FILL AND ITEM 613.10, STONE FILL, TYPE I AS DIRECTED BY THE ENGINEER.

**SEEDING FORMULA**

RATE: DOUBLE IF HYDROSEEDING

% WT.	LBS./A.	NAME	PUR %	GERM %
38	57	CREEPING RED FESCUE	98	90
29	43.5	HARD FESCUE	95	85
15	22.5	CHEWINGS FESCUE	95	87
15	22.5	ANNUAL RYE GRASS	95	90
3	4.5	INERTS	--	--
100.0	80 LB/A			

**SEEDING NOTES**

SEED MIXTURE: SHALL NOT HAVE A WEED CONTENT EXCEEDING 0.40% BY WEIGHT AND SHALL BE FREE OF ALL NOXIOUS SEED.

SEED: TO BE APPLIED PER SEEDING FORMULAS OR AS DIRECTED BY THE ENGINEER.

FERTILIZER: FORMULA 10-20-10, TO BE USED WITH SEED, APPLIED AT THE RATE OF 500 LBS./ACRE. (HYDRO SEEDERS MAY USE 19-19-19 FORMULA).

AGRICULTURAL LIMESTONE: TO BE APPLIED AT THE RATE OF 2 TONS/ACRE, OR AS DIRECTED BY THE ENGINEER.

HAY MULCH: TO BE PLACED ON THE EARTH SLOPES AT THE RATE OF 2 TONS/ACRE, OR AS DIRECTED BY THE ENGINEER.

TOPSOIL: TO BE USED WITH SEED AS INDICATED ON THE PLANS, OR AS DIRECTED BY THE ENGINEER.

PROJECT NAME: LEMINGTON-CANAAN  
 PROJECT NUMBER: STP 2723(1)

FILE NAME: z07c214frm.dgn PLOT DATE: 2/28/2015  
 PROJECT LEADER: P. SHEDD DRAWN BY: W. GORDON  
 DESIGNED BY: N. LEMAY CHECKED BY: P. SHEDD  
 DITCH CLEANING DETAIL SHEET 2 SHEET 23 OF 162