

**STATE OF VERMONT
AGENCY OF TRANSPORTATION**

ITEM DETAIL SUMMARY SHEET 3

BEGIN STATION	END STATION	POS.	203.15 COMMON EXCAV. CY	203.16 SOLID ROCK EXCAV. CY	203.30 EARTH BORROW CY	204.22 TRENCH EXCAV. OF EARTH, EXP. (N.A.B.I.) CY	301.26 SUBBASE OF CRUSHED GRAVEL CY	604.40 CHANGE ELEV. D1 EACH	604.412 REHAB. D. I. CLASS I EACH	604.415 REHAB. D. I. CLASS II EACH	604.418 REHAB. D. I. CLASS III EACH	604.42 CHANGE ELEV. SEWER MANHOLE EACH	616.21 VERTICAL GRANITE CURB LF	616.28 CAST-IN-PLACE CONC CURB, TYPE B LF	616.41 REMOVAL OF EXISTING CURB LF	618.10 P.C.C. SIDE-WALK, 5 INCH SY	618.30 DETECTABLE WARNING SURFACE SF							REMARKS	
54+76	54+91	LT	1.15	0.96			1.15							23	23	6.92	32							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES	
54+78	54+90	RT	1.15	0.96			1.16									6.95	20							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 5, EXAMPLE 2 FROM STANDARD DRAWING C-3A	
58+17	58+37	LT												30	30										
58+21	58+26	RT	0.46	0.39			0.46							5	5	2.78	8								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
58+78	58+89	LT	1.98	1.65			1.98							19	19	11.88	24								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
58+82	58+87	RT	0.46	0.39			0.46							5	5	2.78	8								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
61+27	61+34	RT	0.74	0.62			0.74							5	5	4.43	10								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
61+64	61+74	RT	0.77	0.64			0.77							5	5	4.60	12								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
62+27	62+39	LT	0.91	0.76			0.91							5	5	5.46	26								REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
62+29	62+38	RT	0.72	0.60			0.72							9	9	4.34	10								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
62+79	62+92	LT	2.12	1.77			2.12									12.73	28								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
62+84	62+92	RT	0.68	0.57			0.68							9	9	4.09	10								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
63+21	64+43	LT					32.11							122	126	96.32									REMOVE EXISTNG CURB AND PAVEMENT. CONSTRUCT NEW SIDEWALK AND CURB
66+37	66+53	LT	1.32	1.10			1.32							26	26	7.93	34								REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
66+40	66+54	RT	1.58	1.32			1.58							24	24	9.51	32								REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
66+94	67+08	RT	1.76	1.46			1.76							22	22	10.53	32								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
66+99	67+12	LT	2.81	2.34			2.81									16.84	28								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
73+08	73+19	RT	1.00	0.83			1.00									6.00	28								REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
73+10	73+20	LT	0.85	0.71			0.85									5.09	24								REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
73+46	73+48	RT												5	5										
73+47	73+51	LT	0.34	0.29			0.34							5	5	2.07	8								REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
SUBTOTAL			20.80	17.36	-	-	52.92	-	-	-	-	-	-	319	323	221.25	374								

ITEM DETAIL SUMMARY SHEET 3	PROJECT NAME: BURLINGTON (CLASS I)
	PROJECT NUMBER: STP 2722 (I)
	FILE NAME: 07d028.dgn
	PLOT DATE: 05-JUN-2014 11:20
PROJECT LEADER: CDL	DRAWN BY: SJL
DESIGNED BY: SJL	CHECKED BY: EPD
PLOT FILE: 07d028_13.i	SHEET 13 OF 61