

**STATE OF VERMONT  
AGENCY OF TRANSPORTATION**

**ITEM DETAIL SUMMARY SHEET 4**

BEGIN STATION	END STATION	POS.	203.15 COMMON EXCAV.	203.16 SOL ID ROCK EXCAV.	203.30 EARTH BORROW	204.22 TRENCH EXCAV. OF EARTH, EXP. (N. A. B. I.)	301.26 SUBBASE OF CRUSHED GRAVEL	604.40 CHANGE ELEV. D1	604.412 REHAB. D. I. CLASS I	604.415 REHAB. D. I. CLASS II	604.418 REHAB. D. I. CLASS III	604.42 CHANGE ELEV. SEWER MANHOLE	616.21 VERTICAL GRANITE CURB	616.28 CAST- IN PLACE CONC CURB, TYPE B	616.41 REMOVAL OF EXISTING CURB	618.10 P. C. C. SIDE-WALK, 5 INCH	618.30 DETECTABLE WARNING SURFACE							REMARKS
			CY	CY	CY	CY	CY	EACH	EACH	EACH	EACH	EACH	LF	LF	LF	SY	SF							
73+47	73+53	RT	0.52	0.43			0.52									3.12	8							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
73+51	73+56	LT	0.72	0.60			0.72							7	7	4.32	8							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
73+53	73+58	RT	0.67	0.56			0.67							5	5	4.01	8							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
86+30	86+42	LT	0.94	0.78			0.94									5.62	12							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
86+68	86+81	LT	1.03	0.86			1.03									6.16	14							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
89+19	89+27	RT	0.76	0.64			0.76									4.57	22							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
89+29	89+39	LT	0.85	0.71			0.85									5.08	24							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
89+50	89+58	RT	0.58	0.49			0.58									3.51	8							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
89+66	89+77	LT	0.83	0.69			0.83									5.00	24							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
89+77	89+87	RT	0.54	0.45			0.54									3.27	12							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
92+05	92+13	RT	0.86	0.72			0.86						6			5.16	12							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
92+07	92+12	LT	0.69	0.58			0.69									4.14	8							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 2 FROM STANDARD DRAWING C-3A
96+85	96+91	LT	0.30	0.25			0.30							6	6	1.81	8							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
96+92	96+95	LT	0.30	0.25			0.30							6	6	1.81	8							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
97+49	97+72	RT	1.95	1.63			1.95									11.70	32							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
97+52	97+76	LT	1.39	1.16			1.39									8.35	40							REPLACE CONCRETE REQUIRED FOR INSTALLATION OF TRUNCATED DOMES
98+16	98+28	RT	2.04	1.70			2.04							14	14	12.22	20							REMOVE AND RECONSTRUCT SIDEWALK RAMP TYPE 6, EXAMPLE 3 FROM STANDARD DRAWING C-3B
<b>SUBTOTAL THIS SHEET</b>			14.97	12.5	-	-	14.97	-	-	-	-	-	6	38	38	89.85	268							
<b>SUBTOTAL SHEET 11</b>			71.03	31.75	25	1	42.35	28	46	6	5	38	-	186	76	239.78	340							
<b>SUBTOTAL SHEET 12</b>			26.42	22.01	-	-	26.61	-	-	-	-	-	-	38	38	159.64	415							
<b>SUBTOTAL SHEET 13</b>			20.80	17.36	-	-	52.92	-	-	-	-	-	-	319	323	221.25	374							
<b>ROUNDING</b>			6.78	0.38	-	-	3.15	-	-	-	-	-	9	5	5	9.48	3							
<b>GRAND TOTAL</b>			140	85	25	1	140	28	46	6	5	38	6	590	480	720	1400							

**ITEM  
DETAIL  
SUMMARY  
SHEET 4**

PROJECT NAME: BURLINGTON (CLASS I)  
PROJECT NUMBER: STP 2722 (I)  
FILE NAME: 07d028.dgn  
PROJECT LEADER: CDL  
DESIGNED BY: SJL  
PLOT FILE: 07d028\_14.i  
PLOT DATE: 05-JUN-2014 11:20  
DRAWN BY: SJL  
CHECKED BY: EPD  
SHEET 14 OF 61