



- NOTES.
- FOR A PLAN VIEW OF FOOTING REINFORCEMENT SEE SHEET BR910.
 - THE AVERAGE PILE LENGTH IS APPROXIMATELY 30 FEET.
 - I~ INDICATES LOCATION OF A VERTICAL PILE.
I~ INDICATES LOCATION AND DIRECTION OF A LONG BATTERED PILE.
 - PILES SHALL BE DRIVEN TO LEDGE OR TO A CAPACITY OF 140K AND SHALL HAVE REINFORCED TIPS (AS PER SPECIFICATION 505.04f.)

STATE OF VERMONT	
AGENCY OF TRANSPORTATION	
TOWN OF WATERFORD	Bridge No. 9
HIGHWAY NO. 118	Log Sta. Surv. Sta. 150+00
VT 118 OVER I-93	
DETAILS FOR WINGWALLS 1&2 AND PILE LAYOUT	
Designed by D.E. LATHROP	Drawn by C. BENDA/DW.
Checked by M. CERUTTI date 7/80	Bridge Design Supervisor E.L. DeHoy date 7/80
PROJECT WATERFORD	PROJECT NO. I-93-1(2) CONT. 3
Bridge Sheet No. BR 911	Sheet 187 of 531

STATEWIDE - N.E. REGION
 BHF MEMB(19)
 SHEET 72 OF 80
 BRIDGE No. 9
 FOR REFERENCE ONLY