

**STATE OF VERMONT  
AGENCY OF TRANSPORTATION**

**ITEM DETAIL SUMMARY SHEET 1**

BEGIN STATION	END STATION	POS.	201.31 THIN AND TRIM SIGNS	203.15 COMMON EXCAV.	203.16 SOLID ROCK EXCAV.	203.30 EARTH BORROW	204.22 TRENCH EXCAV. OF EARTH, EXP. (N.A.B.I.)	301.28 SUBBASE OF GRAVEL FINE GR.	402.12 AGG. SHOULD.	601.2615 18' CPEP (SL)	604.10 CONC. CATCH BASIN W/GRATE	604.412 REHAB. D. I. CLASS I	604.415 REHAB. D. I. CLASS II	604.42 CHANGE ELV. OF SMH	613.10 STONE FILL TYPE 1	616.41 REMOVAL OF EXISTING CURB	619.17 YIELDING MARKER POSTS	621.20 STEEL BEAM G.R., GALV	621.205 STEEL BEAM G.R., GALV W/8FT POSTS	621.217 HD STEEL BEAM G.R., GALV/NEST W/8FT POSTS	621.60 ANCHOR FOR STEEL BEAM RAIL	621.80 REMOVE & DISP. OF G.R.	629.20 ADJUST ELEV. VALVE BOX	649.31 GEO. UNDER STONE FILL	676.10 DELINE. WITH STEEL POSTS	676.12 REMOVAL OF EXIST. DELINE.	REMARKS		
			EA	CY	CY	CY	CY	TON	TON	LF	EACH	EACH	EACH	EACH	CY	LF	EACH	LF	LF		EACH	LF	EACH	SY	EACH	EACH			
NEWPORT																													
126+46	276+66	LT&RT	3	<b>1084</b>	1646.3	25	1	7138.2	607	10	2	10	2	1	692		43												ESTIMATED QUANTITIES TO BE USED AS DIRECTED BY THE RESIDENT ENGINEER.
				△																									
164+75	164+85	LT													5														REPAIR ERODED AREA.
210+75.5	213+92	RT							10									216.5	100		2	252			2	2		INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 210+75.5 AND STA. 213+92.	
211+40	214+94	LT							10									354			2	352			2	2		INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 211+40 AND STA. 214+94.	
221+85.5	1224+00	RT/LT							5									239.5	200		1	440			1	1		CONNECT TO EXISTING GUARDRAIL AT ROUTE 100 PAVING LIMIT. INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 221+85.5 RT	
224+49	225+23	LT&RT		<b>12</b>				118.2																					REMOVE EXISTING RAISED ISLAND.
				△																									
227+73	243+02	LT							10									177	1352		2	1518			2	2		INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 227+73 LT AND STA. 243+02 LT.	
231+23		RT			8.7																								REMOVE EXISTING CATCH BASIN.
230+41	240+25	RT		<b>194</b>	17.4																								REMOVE BITUMINOUS CONCRETE GUTTER AND TWO CATCH BASINS.
				△																									
257+19	258+99.25	RT							10										139.5	50	2					2		INSTALL 25'-0" LONG, 16' RADIUS WITH ANCHOR AT STA. 257+19 RT AND INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 259+00 RT.	
SUBTOTAL			3	<b>1290</b>	1672.4	25	1	7256.4	652	10	2	10	2	1	697	153	43	987	1791.5	50	9	2562	2	3087.2	9	7			
				△																									

REVISION	BY	DATE
△	KML	9-27-2011

REVISION NO. 1 - REVISED QUANTITY OF ITEM 203J5 FOR EXCAVATION ADJACENT TO CONCRETE SLABS AS DIRECTED BY THE RESIDENT ENGINEER.

**ITEM  
DETAIL  
SUMMARY  
SHEET 1**

PROJECT NAME: NEWPORT-COVENTRY-NEWPORT  
 PROJECT NUMBER: STP 2802(I)  
 FILE NAME: IPARM.dgn  
 PROJECT LEADER: CDL  
 DESIGNED BY: RHB  
 PLOT FILE: 08b158-14.1  
 PLOT DATE: 27-SEP-2011  
 DRAWN BY: SJL  
 CHECKED BY: EPD  
 SHEET 14 OF 134