

# ITEM DETAIL SUMMARY SHEET 3

LOCATION			GUARDRAIL							MISCELLANEOUS											REMARKS	
BEGIN MILE STA.	END MILE STA.	POS.	621.20	621.205	621.207	621.21	621.50	621.60	621.70	621.80	203.30	402.12	601.0910	604.412	613.10	613.11	616.35	616.47	617.10	617.12		619.17
			S.B. G.R. GALV. LF	S.B. G.R. GALV. 8' POST LF	S.B. G.R. GALV./NEST. W/8' POSTS LF	H.D. S.B. G.R. GALV. LF	MTS, FLARED EA	ANCHOR FOR S.B. RAIL EA	G.R. APP. SECTION GALV. TYPE I EA	REMOVAL & DISPOSAL OF GUARDRAIL LF	EARTH BORROW CY	AGG. SHLDRS. TON	15" CPEP LF	REHAB DI, CB, OR MH, CLASS I EA	STONE FILL, TYPE I CY	STONE FILL, TYPE II CY	TREATED TIMBER CURB LF	BIT. CONC. GUT. & TRAFF. ISL. TON	RELOC. MAILBOX, SNGL. SUPP. EACH	RELOC. MAILBOX, MULT. SUPP. EACH		YIELDING MARKER POSTS EACH
VT ROUTE 128																						
WESTFORD	FAIRFAX																					
271+24		RT																				
272+14		LT																				
273+31.5	279+06.5	LT	354	200	25			2		365			20								1	
INSTALL ANCHOR @ 273+31.5, LT AND 279+06.5, LT (SEE BOTH DETAILS ON GUARDRAIL DETAIL SHEET #1) RELOCATE MAILBOX MULTIPLE SUPPORT AT STA. 274+58, LT																						
274+81.5	277+31.5	RT	152	37.5	25		1	1		190	25											
INSTALL ANCHOR @ 274+81.5, RT, INSTALL M.T.S., FLARED @ 276+94, RT (SEE GUARDRAIL AT LARGE CULVERT DETAIL ON GUARDRAIL DETAIL SHEET #1)																						
275+07		LT													1.1							
ITEMS TO BE USED WITH SLOPE EROSION REPAIR.																						
279+55		LT																			1	
281+40		LT																			1	
282+05		LT																			1	
285+20		RT																			1	
288+25		LT																			1	
302+93	303+93	RT	104					2		98							89					
INSTALL ANCHOR @ 302+93, RT AND 303+93, RT; INSTALL TREATED TIMBER CURB @ STA. 303+00 TO 303+89, RT																						
304+17		RT																			1	
304+27		RT																			1	
318+30		LT																			1	
322+24		RT																			1	
329+93		RT																			1	
335+22		LT																			1	
335+89		RT																			1	
337+55		LT																			1	
337+57		LT																			1	
341+76		RT																			1	
342+21		LT																			1	
344+76		LT																			1	
344+80		LT																			1	
344+82		LT																			1	
345+65		LT																			1	
FAIRFAX																						
0+38		RT																			1	
2+07		LT																			1	
3+11		LT																			1	
7+44	11+02	LT	100					2		2	284	50					35	0.5				
INSTALL M.T.S., FLARED @ 7+44, LT AND 10+56.5, LT; SEE BRIDGE DETAIL SHEET NO.3; INSTALL TREATED TIMBER CURB FROM 9+44 TO 9+79, LT; CONSTRUCT BITUMINOUS CONCRETE GUTTER FROM 9+44 TO 9+79, LT																						
<b>ITEM DETAIL SUMMARY SHEET #3</b>			PROJECT NAME: WESTFORD - FAIRFAX PROJECT NUMBER: STP 2804(1) FILE NAME: p08c212.dgn PROJECT LEADER: JLL DESIGNED BY: STANTEC IPARM FILE: p08c212ids03.i PLOT DATE: 31-OCT-2012 13:56 DRAWN BY: STANTEC CHECKED BY: JLL SHEET 10 OF 79																			
SHEET SUBTOTALS:			710	237.5	50	-	3	5	2	937	75	-	20	-	1.1	-	124	0.5	24	2	-	