

ITEM DETAIL SUMMARY SHEET #3

| LOCATION | | | GUARDRAIL | | | | | | | | | | CURB | | | MISCELLANEOUS | | | | | | | | | | REMARKS | | |
|-----------------------|-------------|------|----------------|------------------------------|-------------------|--------------------------|--------------------------------------|---------------------|-------------------------------|--------------------------------|-------------------|-----------------------|--------------------|----------------|---------------------------|--------------------|--------------------------|---------|---------|--------------------|-----------------------|--------|-----------------|-----------------------|-------------|-----------------|---|--|
| BEGIN STATION | END STATION | POS. | 621.20 | 621.205 | 621.21 | 621.216 | 621.217 | 621.60 | 621.70 | 621.71 | 621.75 | 621.80 | 616.20 | 616.21 | 616.305 | 301.28 | 604.412 | 604.415 | 604.418 | 613.10 | 649.51 | 651.15 | 651.40 | 653.20 | 653.60 | 676.10 | | |
| | | | S.B. GR. GALV. | S.B. GR. GALV. W/ 8 FT POSTS | HD S.B. GR. GALV. | HD S.B. GR. GALV. NESTED | HD S.B. GR. GALV./ NESTED 8 FT POSTS | ANCR. FOR S.B. RAIL | GR APP. SECTION. GALV. TYPE I | GR APP. SECTION. GALV. TYPE II | REMOVE & RESET GR | REMOVAL & DISP. OF GR | GRAN. SLOPE EDGING | VERT GRAN CURB | BITUM. CONC. CURB. TYPE A | SUB. OF C.G., F.G. | REHAB. DI'S CB'S OR MH'S | | | STONE FILL. TYPE I | GEOTEX FOR SILT FENCE | SEED | GRUB. MAT. (6") | TEMP. EROSION MATTING | EROSION LOG | DEL W/ ST. POST | | |
| | | | LF | LF | LF | LF | LF | EA | EA | EA | LF | LF | LF | LF | LF | TON | EA | EA | EA | CY | SY | LB | SY | SY | LF | EA | | |
| STOCKBRIDGE: | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 197+56.5 | 199+23.0 | RT | 66.5 | | 73.95 | | | 2 | | | | 125.0 | | | | | | | | | | | | | 50.0 | 2 | SEE VTRANS STANDARD SHEET G-ID. PROVIDE ANCHORS AT STA 197+63.0 AND STA 199+16.5. CONNECT NEW HD STEEL BEAM GUARDRAIL TO BRIDGE RAIL AT STA 198+21.0 AND END AT STA 198+58.5. SEE SHEET 396 FOR BR IO DETAILS. | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 197+86.0 | 200+17.0 | LT | 129.0 | | 73.75 | | | 2 | | | | 187.5 | | | | | | | | | | | | | 50.0 | 2 | SEE VTRANS STANDARD SHEET G-ID. PROVIDE ANCHORS AT STA 197+94.5 AND STA 200+10.5. CONNECT NEW HD STEEL BEAM GUARDRAIL TO BRIDGE RAIL AT STA 198+40.0 AND END AT STA 198+77.5. SEE SHEET 396 FOR BR IO DETAILS. | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 202+29.0 | 219+45.5 | LT | 189.5 | 1364.0 | | | | 2 | | | 300.0 | 1437.5 | | 845.0 | | | | | | 332.51 | | | | | | | 2 | SEE VTRANS STANDARD SHEET G-ID. PROVIDE ANCHORS AT STA 202+35.5 AND STA 219+39.0. SEE SHEET 25 FOR SIDE SLOPE TREATMENT DETAILS. |
| 205+88.0 | 206+28.0 | RT | | 1379.0 | | | | | | | | | | | | | | | | 40.7 | | 10.3 | 370.6 | 603.1 | | | | |
| | | | | | | | | | | | | | | | | | | | | | 192.54 (TYPE II) | | | | | | | |
| 219+83.0 | 232+55.0 | LT | 1152.0 | | | | | | | | 137.5 | 1150.0 | | 380.0 | | | | | | 256.09 | | | | | | | 1 | SEE VTRANS STANDARD SHEET G-ID. PROVIDE ANCHOR AT STA 219+89.5. CONNECT NEW STEEL BEAM GUARDRAIL TO EXISTING RAIL AT STA 232+60.0 ON BRIDGE STREET. SEE SHEET 25 FOR SIDE SLOPE TREATMENT DETAILS. SEE SHEET 26 FOR CURB REMOVAL AND STONE FILL BACKING DETAILS. |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 232+84.0 | 246+95.0 | | 1339.5 | | | | | | | | 125.0 | 1662.5 | | | | | | | | | | | | | | | | |
| 232+89.0 | 250+13.0 | LT | 839.5 | | | | | + 2 | | | 525.0 | 1199.0 | | | | | | | | | | 0.6 | | 37.8 | | 1 | CONNECT NEW STEEL BEAM GUARDRAIL TO EXISTING RAIL AT STA 232+89.0 ON BRIDGE STREET. SEE VTRANS STANDARD SHEET G-ID. PROVIDE ANCHOR AT STA 246+47.0. SEE SHEET 25 FOR SIDE SLOPE TREATMENT DETAILS. | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 259+37.0 | 267+87.0 | LT | 654.0 | | | | | 2 | | | | 850.0 | | | | | | | | | | | | | 50.0 | 2 | SEE VTRANS STANDARD SHEET G-ID. PROVIDE ANCHORS AT STA 260+06.5 AND STA 266+47.5. | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 277+50.0 | 280+50.0 | RT | | | | | | | | | | | | | | | | | | | 27.16 | | | | | | | |
| 278+25.0 | 278+50.0 | LT | | 511.5 | | | | | | | 2225.0 | 475.0 | | | | | | | | | 11.0 | 1.4 | 26.4 | 81.7 | | | | |
| 286+79.0 | 313+91.5 | LT | 39.5 | 282.5 | | | | 2 | | | 2450.0 | 262.5 | | | | | | | | | 3.47 | | | | | | 2 | SEE VTRANS STANDARD SHEET G-ID. SEE SHEET 25 FOR REDUCED POST SPACING AT UTILITY POLE DETAILS. |
| 286+68.0 | 313+87.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 292+00.0 | 293+50.0 | RT | | | | | | | | | | | | | | | | | | | | 0.4 | | 25.0 | | | | |
| 300+50.0 | 303+50.0 | RT | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 307+00.0 | 307+50.0 | RT | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 316+00.0 | 319+00.0 | LT | | | | | | | | | | | | | | | | | | | | 1.0 | 60.3 | 60.3 | | | | |
| 321+00.0 | 322+00.0 | RT | | | | | | | | | | | | | | | | | | | | 0.5 | | 31.7 | | | | |
| THIS SHEET SUBTOTALS: | | | 2491.0 | 1661.5 | 130.0 | - | - | 10 | - | - | 3812.5 | 4749.0 | - | - | 1366.0 | 18.0 | - | - | - | 622.98 | | | | | | | | |

14

192.54 (TYPE II)

| | |
|---|----------------------------------|
| ITEM DETAIL SUMMARY SHEET #3 | PROJECT NAME: STOCKBRIDGE-BETHEL |
| | PROJECT NUMBER: STP 2910(1) |
| | FILE NAME: z10b214_ids.03.dgn |
| | PLOT DATE: 3/17/2014 |
| DESIGNED BY: L.M.B. | CHECKED BY: J.P.S. |
| IPARM FILE: z10b214ids3.i | SHEET 16 OF 397 |

FILE NAME = \\1570\projects\1570\22426\CADD\1570\z10b214_ids.03.dgn
 DATE = 3/17/2014
 USER = LMB