

FILE NAME = \\172\projects\14\1422426\CADD\1.MST\14\10b214_cotpp_02.dgn
 DATE = 3/17/2014
 USER = J.P.S.

EXISTING GUARDRAIL INVENTORY								PROTECTION PLAN	
BEGIN STA.	END STA.	OFFSET	LENGTH (LF)	RETAIN/REPLACE (Y/N)	APPROX. OFFSET DISTANCE FROM PROPOSED CENTERLINE TO FACE OF EXISTING RAIL (LF)	EXISTING RAIL TYPE (POST AND BARRIER)	ASSESSED CONDITION (GOOD/FAIR/POOR)	CONSTRUCTION CONDITION	900.640 BARRIER FOR TEMPORARY TRAFFIC PROTECTION (LF)
197+86.0	198+40.0	LT	54	Y	20-22	STEEL W-BEAM	POOR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
198+58.5	199+15.0	RT	56.5	Y	18-27	STEEL W-BEAM	POOR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
198+77.5	200+15.0	LT	137.5	Y	18-30	STEEL W-BEAM	POOR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
202+37.0	219+37.0	LT	1700	Y	15-20	STEEL W-BEAM	POOR	202+37 +/- TO 209+00 +/- REMOVE BEFORE SHOULDER RECONSTRUCTION AND DELINEATE WITH BARRELS. 209+00 +/- TO 219+37 +/- LEAVE IN PLACE FOR ALL OPERATIONS. INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS LIFT IS COMPLETE.	1687.0
219+91.0	232+55.0	LT	1404	Y	19-22	STEEL W-BEAM	POOR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
232+89.0	250+13.0	LT	1864	Y	19-22	STEEL W-BEAM	FAIR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
259+37.0	267+87.0	LT	850	Y	20-23	STEEL W-BEAM	FAIR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
286+79.0	313+91.5	LT	2712.5	Y	13-15	STEEL W-BEAM	GOOD	REMOVE AND RESET TO FACE OF RAIL 17 FEET OFF PROPOSED CENTERLINE BEFORE SHOULDER RECONSTRUCTION AND REMOVE AND RESET AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE. WOOD POSTS TO BE REPLACED WITH SALVAGED STEEL POSTS FOR TEMPORARY CONFIGURATION DURING CONSTRUCTION.	2700.0 2712.5
337+42.0	338+26.0	RT	84	Y	14-15	STEEL W-BEAM	POOR	REMOVE AND RESET TO FACE OF RAIL 17 FEET OFF PROPOSED CENTERLINE BEFORE SHOULDER RECONSTRUCTION AND REMOVE AND RESET AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	87.5 84
337+46.5	353+84.48	LT	1637.98	Y	14-16	STEEL W-BEAM	FAIR	REMOVE AND RESET TO FACE OF RAIL 17 FEET OFF PROPOSED CENTERLINE BEFORE SHOULDER RECONSTRUCTION AND REMOVE AND RESET AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	1499.5 1638
Bethel Route 107									-
B 0+00.0	B 11+13.0	LT	1113	Y	14-16	STEEL W-BEAM	GOOD	REMOVE AND RESET TO FACE OF RAIL 17 FEET OFF PROPOSED CENTERLINE BEFORE SHOULDER RECONSTRUCTION AND REMOVE AND RESET AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	1113
B 17+15.0	B 32+14.0	LT	1499	Y	12-15	STEEL W-BEAM	FAIR	REMOVE AND RESET TO FACE OF RAIL 17 FEET OFF PROPOSED CENTERLINE BEFORE SHOULDER RECONSTRUCTION AND REMOVE AND RESET AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	425.0 1499
B 34+64.0	B 36+95.0	LT	231	Y	14-16	STEEL W-BEAM	POOR	REMOVE BEFORE SHOULDER RECONSTRUCTION AND DELINEATE WITH BARRELS AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS LIFT IS COMPLETE.	237.5
B 41+89.0	B 58+17.0	LT	1628	Y	12-20	STEEL W-BEAM	POOR	REMOVE BEFORE SHOULDER RECONSTRUCTION AND DELINEATE WITH BARRELS AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS LIFT IS COMPLETE.	1362.5
B 61+56.0	B 67+60.0	LT	604	N	21-23	STEEL W-BEAM	POOR	REMOVE BEFORE SHOULDER RECONSTRUCTION.	-
B 74+93.0	B 83+53.0	LT	860	N	19-20	STEEL W-BEAM	FAIR	REMOVE BEFORE SHOULDER RECONSTRUCTION.	-
B 86+36.5	B 87+18.0	LT	81.5	Y	15-16	STEEL W-BEAM	FAIR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-
B 86+40.0	B 87+10.0	RT	70	Y	15-16	STEEL W-BEAM	POOR	LEAVE IN PLACE FOR ALL OPERATIONS AND REMOVE AND INSTALL NEW AFTER COLD MIX LIFT OR TYPE IIIS IS COMPLETE.	-

CONSTRUCTION OPERATIONS TRAFFIC PROTECTION PLAN SHEET #2	PROJECT NAME: STOCKBRIDGE-BETHEL
	PROJECT NUMBER: STP 2910(1)
	FILE NAME: z10b214_cotpp_02.dgn
	DESIGNED BY: L.M.B.
	PLOT DATE: 3/17/2014
	DRAWN BY: W.G.P.
	CHECKED BY: J.P.S.
	SHEET 389 OF 397