

Element	Point Type	Station	Northing	Easting	Radius	Length	Delta / Theta	Rotation Direction	Maximum Banking	Design Speed
Tangent	POB	488+07.04	783820.83	1554477.73						
	PC	492+67.34	784167.17	1554780.93						
Arc	PC	492+67.34	784167.17	1554780.93	803.8	469.85	33°29'28"	Left	0.060	50
	PI	495+09.19	784349.14	1554940.24						
	CC		784696.63	1554176.14						
	PT	497+37.19	784588.80	1554972.68						
Tangent	PT	497+37.19	784588.80	1554972.68						
	PC	499+03.82	784753.92	1554995.03						
Arc	PC	499+03.82	784753.92	1554995.03	1200	139.11	6°38'31"	Right	0.055	50
	PI	499+73.45	784822.92	1555004.38						
	CC		784592.94	1556184.19						
	PT	500+42.93	784890.38	1555021.64						
Tangent	PT	500+42.93	784890.38	1555021.64						
	PC	500+96.53	784942.32	1555034.92						
Arc	PC	500+96.53	784942.32	1555034.92	850	342.66	23°05'52"	Left	0.06	50
	PI	502+70.22	785110.58	1555077.98						
	CC		785153.01	1554211.45						
	PT	504+39.19	785282.25	1555051.56						
Tangent	PT	504+39.19	785282.25	1555051.56						
	PC	509+88.93	785825.60	1554967.97						
Arc	PC	509+88.93	785825.60	1554967.97	10000	321.68	1°50'35"	Right	NC	50
	PI	511+49.78	785984.58	1554943.51						
	CC		787346.16	1564851.69						
	PT	513+10.61	786144.27	1554924.18						
Tangent	PT	513+10.61	786144.27	1554924.18						
	PC	515+52.22	786384.13	1554895.14						
Arc	PC	515+52.22	786384.13	1554895.14	600	227.59	21°44'00"	Left	0.080	50
	PI	516+67.40	786498.47	1554881.30						
	CC		786312.01	1554299.49						
	PT	517+79.81	786599.56	1554826.10						
Tangent	PT	517+79.81	786599.56	1554826.10						
	PC	519+64.14	786761.35	1554737.76						
Arc	PC	519+64.14	786761.35	1554737.76	1500	248.33	9°29'08"	Right	0.062	50
	PI	520+88.59	786870.58	1554678.11						
	CC		787480.23	1556054.27						
	PT	522+12.47	786988.14	1554637.29						
Tangent	PT	522+12.47	786988.14	1554637.29						
	PC	523+36.40	787105.20	1554596.63						
Arc	PC	523+36.40	787105.20	1554596.63	2000	233.22	6°40'53"	Left	0.051	50
	PI	524+53.14	787215.49	1554558.33						
	CC		786449.08	1552707.32						
	PT	525+69.62	787320.57	1554507.46						
Tangent	PT	525+69.62	787320.57	1554507.46						
	PC	527+52.83	787485.47	1554427.63						
Arc	PC	527+52.83	787485.47	1554427.63	660	478.77	41°33'46"	Right	0.060	50
	PI	530+03.30	787710.91	1554318.49						
	CC		787773.06	1555021.68						
	PT	532+31.60	787951.99	1554386.40						
Tangent	PT	532+31.60	787951.99	1554386.40						
	PC	544+82.86	789156.39	1554725.63						
Arc	PC	544+82.86	789156.39	1554725.63	3200	288.16	5°09'34"	Left	0.035	50
	PI	546+27.04	789295.17	1554764.72						
	CC		790023.95	1551645.47						
	PT	547+71.02	789436.90	1554791.17						
Tangent	PT	547+71.02	789436.90	1554791.17						
	PC	548+97.95	789561.67	1554814.45						
Arc	PC	548+97.95	789561.67	1554814.45	5000	436.09	4°59'50"	Right	0.024	50
	PI	551+16.13	789776.15	1554854.48						
	CC		788644.40	1559729.59						
	PT	553+34.04	789986.32	1554913.03						
Tangent	PT	553+34.04	789986.32	1554913.03						
	PC	555+05.18	790151.19	1554958.96						

Element	Point Type	Station	Northing	Easting	Radius	Length	Delta / Theta	Rotation Direction	Maximum Banking	Design Speed
Arc	PC	555+05.18	790151.19	1554958.96	7500	328.05	2°30'22"	Left	0.020	50
	PI	556+69.23	790309.22	1555002.99						
	CC		792164.07	1547734.12						
	PT	558+33.23	790469.03	1555040.07						
Tangent	PT	558+33.23	790469.03	1555040.07						
	PC	558+78.21	790512.85	1555050.24						
Arc	PC	558+78.21	790512.85	1555050.24	30000	401.30	0°45'59"	Left	NC	50
	PI	560+78.87	790708.31	1555095.59						
	CC		797293.01	1525826.45						
	PT	562+79.51	790904.36	1555138.32						
Tangent	PT	562+79.51	790904.36	1555138.32						
	PC	564+15.55	791037.28	1555167.28						
Arc	PC	564+15.55	791037.28	1555167.28	1500	297.79	11°22'29"	Right	0.062	50
	PI	565+64.93	791183.23	1555199.10						
	CC		790717.84	1556632.88						
	PT	567+13.34	791320.05	1555259.07						
Tangent	PT	567+13.34	791320.05	1555259.07						
	PC	575+06.67	792046.64	1555577.57						
Arc	PC	575+06.67	792046.64	1555577.57	1300	293.16	12°55'15"	Left	0.067	50
	PI	576+53.88	792181.47	1555636.67						
	CC		792568.56	1554386.94						
	PT	577+99.84	792326.09	1555664.13						
Tangent	PT	577+99.84	792326.09	1555664.13						
	PC	579+15.45	792439.68	1555685.69						
Arc	PC	579+15.45	792439.68	1555685.69	5000	108.71	1°14'45"	Right	0.020	50
	PI	579+69.81	792493.08	1555695.83						
	CC		791507.11	1560597.95						
	PT	580+24.16	792546.25	1555707.13						
Tangent	PT	580+24.16	792546.25	1555707.13						
	PC	580+78.67	792599.57	1555718.45						
Arc	PC	580+78.67	792599.57	1555718.45	680	384.15	32°22'04"	Left	0.080	50
	PI	582+76.02	792792.61	1555759.47						
	CC		792740.89	1555053.30						
	PT	584+62.81	792977.61	1555690.77						
Tangent	PT	584+62.81	792977.61	1555690.77						
	PC	587+89.38	793283.75	1555577.08						
Arc	PC	587+89.38	793283.75	1555577.08	1265	285.63	12°56'13"	Right	0.068	50
	PI	589+32.81	793418.21	1555527.15						
	CC		793724.13	1556762.95						
	PCC	590+75.01	793560.43	1555508.59						
	PCC	590+75.01	793560.43	1555508.59						
	PI	591+73.84	793658.42	1555495.80						
	CC	0	793668.23	1556334.59	833	196.74	13°31'55"	Right	0.079	50
	PT	592+71.75	793756.69	1555506.30						
Tangent	PT	592+71.75	793756.69	1555506.30						
	PC	594+91.46	793975.16	1555529.63						
Arc	PC	594+91.46	793975.16	1555529.63	1000	418.71	23°59'25"	Right	0.076	50
	PI	597+03.93	794186.43	1555552.19						
	CC		793868.96	1556523.97						
	PT	599+10.17	794370.27	1555658.71						
Tangent	PT	599+10.17	794370.27	1555658.71						
	PC	601+06.40	794540.06	1555757.08						
Arc	PC	601+06.40	794540.06	1555757.08	980	663.97	38°49'08"	Left	0.059	50
	PI	604+51.70	794838.84	1555930.18						
	CC		795031.35	1554909.12						
	PT	607+70.37	795180.13	1555877.76						
Tangent	PT	607+70.37	795180.13	1555877.76						
	PC	611+47.73	795553.11	1555820.47						

Element	Point Type	Station	Northing	Easting	Radius	Length	Delta / Theta	Rotation Direction	Maximum Banking	Design Speed
Arc	PC	611+47.73	795553.11	1555820.47	18000	775.21	2°28'03"	Right	NC	50
	PI	615+35.39	795936.28	1555761.61						
	CC		798285.84	1573611.82						
	PT	619+22.93	796321.63	1555719.31						
Tangent	PT	619+22.93	796321.63	1555719.31						
	PC	619+27.41	796326.08	1555718.82						
Arc	PC	619+27.41	796326.08	1555718.82	1800	314.04	9°59'46"	Right	0.046	50
	PI	620+84.83	796482.56	1555701.64						
	CC		796522.50	1557508.07						
	PT	622+41.45	796639.64	1555711.89						
Tangent	PT	622+41.45	796639.64	1555711.89						
	PC	623+18.12	796716.15	1555716.88						
Arc	PC	623+18.12	796716.15	1555716.88	1000	313.43	17°57'30"	Left	0.076	50
	PI	624+76.13	796873.82	1555727.16						
	CC		796781.22	1554719.00						
	PT	626+31.55	797026.99	1555688.33						
Tangent	PT	626+31.55	797026.99	1555688.33						
	PC	629+82.33	797367.02	1555602.12						
Arc	PC	629+82.33	797367.02	1555602.12	4000	4				