



NOTES:

1. COMPACT THE SUBBASE IN THE AREA UNDER THE APPROACH SLAB TO A SMOOTH SURFACE.
2. MATERIAL FOR POLYETHYLENE SHEETING SHALL MEET THE REQUIREMENTS OF SUBSECTION 725.01(c) OF THE STANDARD SPECIFICATIONS. PLACE THE SHEETING ON TOP OF THE FINISHED SUBBASE FOR THE FULL LENGTH AND WIDTH OF THE APPROACH SLAB, AS SHOWN IN THE APPROACH SLAB DETAIL. LAP SHEETING AT LEAST 24 INCHES. PAYMENT INCIDENTAL TO ITEM 501.34 "CONCRETE, HIGH PERFORMANCE CLASS B".
3. POUR APPROACH SLAB CONCRETE IN THE EARLY MORNING BEFORE THE SUPERSTRUCTURE EXPANDS.
4. APPLY 2 COATS TAR EMULSION. PAYMENT INCIDENTAL TO ITEM 501.34 "CONCRETE, HIGH PERFORMANCE CLASS B".

PROJECT NAME:	MIDDLESEX
PROJECT NUMBER:	BRF 024-(K37)
FILE NAME:	sl0c220sup.dgn
PROJECT LEADER:	C. CARLSON
DESIGNED BY:	H. SALLS
APPROACH SLAB DETAILS	
PLOT DATE:	13-JAN-2015
DRAWN BY:	C. BURRALL
CHECKED BY:	H. SALLS
SHEET	23 OF 46