

# PRELIMINARY INFORMATION SHEET (BRIDGE)

LRFD

INDEX OF SHEETS

PLAN SHEETS

1	TITLE SHEET
2	PRELIMINARY INFORMATION SHEET
3	ROADWAY TYPICAL SECTIONS
4	BRIDGE TYPICAL SECTION
5	EARTHWORK TYPICAL SECTIONS
6	CONVENTIONAL SYMBOLOLOGY LEGEND
7-9	QUANTITY SHEETS 1-3
10	PROJECT NOTES
11	TIE SHEET
12	LAYOUT SHEET
13	PROFILE SHEET
14	BRIDGE CONSTRUCTION STAGING
15-16	TRAFFIC CONTROL PLANS 1-2
17	TRAFFIC CONTROL NOTES
18-19	TEMPORARY TRAFFIC BARRIER - BRACED 1-2
20	SIGN SUMMARY SHEET
21	BORING INFORMATION AND LAYOUT SHEET
22-25	BORING LOGS 1-4
26	BRIDGE PLAN & ELEVATION
27-29	NEXT D BEAM DETAILS 1-3
30	BEAM DIAPHRAGM AND DECK DETAILS
31	ELASTOMERIC BEARING DETAILS
32	ABUTMENT 1 MASONRY
33	ABUTMENT 1 REINFORCEMENT
34	ABUTMENT 2 MASONRY
35	ABUTMENT 2 REINFORCEMENT
36	ABUTMENT SECTIONS
37	PIER MODIFICATION
38	CONCRETE SUBSTRUCTURE REPAIR DETAILS
39	APPROACH SLAB DETAILS
40	GUARDRAIL APPROACH AND GUARDRAIL LAYOUT DETAILS
41-43	BRIDGE RAILING DETAILS 1-3
44	REINFORCING STEEL SCHEDULE
45-46	VT 121 - CROSS SECTIONS 1-2
47-51	CHANNEL CROSS SECTIONS 1-5
52	EPSC NARRATIVE
53	EPSC EXISTING CONDITIONS SITE PLAN
54	EPSC CONSTRUCTION CONDITIONS SITE PLAN
55	EPSC FINAL CONDITIONS SITE PLAN
56-58	EPSC DETAIL SHEETS 1-3

STANDARDS LIST

B-5	SLOPE GRADING, EMBANKMENTS, MUCK	06-01-1994
E-121	STANDARD SIGN PLACEMENT - CONVENTIONAL ROAD	08-08-1995
E-123	GUIDE SIGN PLACEMENT - MISCELLANEOUS DETAILS	03-16-2004
E-142	REGULATORY SIGN DETAILS	09-20-1995
E-143	REGULATORY SIGN DETAILS	06-15-2004
E-152	WARNING SIGN DETAILS	05-01-2004
E-160	FLANGED CHANNEL STEEL SIGN POST	05-20-1999
E-161	W-SHAPED STEEL SIGN POST	08-18-1995
E-171A	TRAFFIC CONTROL SIGNALS GENERAL NOTES & DETAILS	08-09-1995
E-171B	TRAFFIC CONTROL SIGNALS MISC. DETAILS	08-09-1995
E-171C	TRAFFIC CONTROL SIGNALS CANTILEVER MOUNTING DETAILS	08-09-1995
E-172	VEHICLE DETECTOR LOOP DETAILS	08-09-1995
E-173	PULL BOXES AND JUNCTION BOXES	08-09-1995
E-175	POWER DROP STANCHIONS	06-08-2009
E-191	PAVEMENT MARKING DETAILS	02-01-1999
E-193	PAVEMENT MARKING DETAILS	08-18-1995
G-1B	BOX BEAM GUARD RAIL	06-01-1994
S-364C	GUARDRAIL APPROACH SECTION, GALVANIZED 3 RAIL BOX BEAM	04-23-2012
S-364D	GUARDRAIL APPROACH SECTION, GALVANIZED 3 RAIL BOX BEAM	04-23-2012
T-1	TRAFFIC CONTROL GENERAL NOTES	08-09-2012
T-10	CONVENTIONAL ROADS CONSTRUCTION APPROACH SIGNING	08-06-2012
T-17	TRAFFIC CONTROL MISCELLANEOUS DETAILS	08-06-2012
T-24	TRAFFIC CONTROL FOR MAINTENANCE PAVEMENT MARKING OPERATION	08-06-2012
T-28	CONSTRUCTION SIGN DETAILS	08-06-2012
T-29	CONSTRUCTION SIGN DETAILS	08-06-2012
T-30	CONSTRUCTION SIGN DETAILS	08-06-2012
T-42	BRIDGE NUMBER PLAQUE	04-09-2014
T-44	MILE MARKER DETAILS STATE AND TOWN HIGHWAYS	04-09-2014
T-45	SQUARE TUBE SIGN POST AND ANCHOR	01-02-2013

REFERENCE SHEETS - EXISTING BRIDGE

59	EXISTING PLANS I - PRELIMINARY INFORMATION
60	EXISTING PLANS II - BORING INFORMATION
61	EXISTING PLANS III - BRIDGE PLAN & ELEVATION
62	EXISTING PLANS IV - DETAILS OF ABUTMENT 1
63	EXISTING PLANS V - DETAILS OF PIER 1 (PIER 2 SIMILAR)
64	EXISTING PLANS VI - DETAILS OF ABUTMENT 2
65	EXISTING PLANS VII - SUPERSTRUCTURE DETAILS
66	EXISTING PLANS VIII - EXPANSION PLATE DETAILS
67	EXISTING PLANS IX - PLAN AND PROFILE (1 OF 2)
68	EXISTING PLANS X - PLAN AND PROFILE (2 OF 2)
69	EXISTING PLANS XI - RETAINING WALL

STRUCTURES DETAIL SHEETS

SD-501.00	CONCRETE DETAILS AND NOTES	5/7/2010
SD-502.00	CONCRETE DETAILS AND NOTES	5/7/2010
SD-516.10	BRIDGE JOINT ASPHALTIC PLUG	8/29/2011

FINAL HYDRAULIC REPORT

HYDROLOGIC DATA

DATE: \_\_\_\_\_  
 DRAINAGE AREA: 70.0 SQ. MI.  
 CHARACTER OF TERRAIN: HILLY TO MOUNTAINOUS VALLEY SETTING  
 STREAM CHARACTERISTICS: STRAIGHT TO SINUOUS, ALLUVIAL,  
 LITTLE TO NO FLOOD PLAN  
 NATURE OF STREAMBED: SAND, GRAVEL, SMALL COBBLES

Q 2.33 = 2850 CFS      Q50 = 8680 CFS  
 Q 10 = 5170 CFS      Q 100 = 10550 CFS  
 Q 25 = 7070 CFS      Q 500 = 16000 CFS

DATE OF FLOOD OF RECORD: AUGUST 28, 2011  
 ESTIMATED DISCHARGE: 20942 CFS  
 WATER SURFACE ELEVATION: 414.6 FT AT GAGE STATION DOWNSTREAM OF BRIDGE  
 NATURAL STREAM VELOCITY: 11.2 FPS @ Q50 = 8680 CFS  
 ICE CONDITIONS: LIGHT TO MODERATE  
 DEBRIS: LIGHT TO MODERATE  
 DOES THE STREAM REACH MAXIMUM HIGHWATER ELEV. RAPIDLY? NO  
 IS ORDINARY RISE RAPID? NO  
 IS STAGE AFFECTED BY UPSTREAM OR DOWNSTREAM CONDITIONS? NO  
 IF YES, DESCRIBE: N/A

WATERSHED STORAGE: <1%      HEADWATERS: -  
 UNIFORM: X  
 IMMEDIATELY ABOVE SITE: -

EXISTING STRUCTURE INFORMATION

STRUCTURE TYPE: 3 SPAN STEEL GIRDER BRIDGE  
 YEAR BUILT: 1954  
 CLEAR SPAN (NORMAL TO STREAM): 157 FT  
 VERTICAL CLEARANCE ABOVE STREAMBED: 28.3 FT (AVG.)  
 WATERWAY OF FULL OPENING: 2220 SQ. FT  
 DISPOSITION OF STRUCTURE: REMOVE ABUTMENT BACKWALL AND SUPERSTRUCTURE  
 TYPE OF MATERIAL UNDER SUBSTRUCTURE: GRAVEL

WATER SURFACE ELEVATIONS AT: ONE BRIDGE LENGTH UPSTREAM

Q 2.33 = 428.7 FT      VELOCITY = 10 FT/SEC  
 Q 10 = 431.0 FT      "      10.7 FT/SEC  
 Q 25 = 432.8 FT      "      11.2 FT/SEC  
 Q50 = 434.0 FT      "      12.4 FT/SEC  
 Q 100 = 435.4 FT      "      13.6 FT/SEC

LONG TERM STREAMBED CHANGES: LITTLE CHANGE SINCE 1953 PLANS

IS THE ROADWAY OVERTOPPED BELOW Q100? NO  
 FREQUENCY: >Q500  
 RELIEF ELEVATION: +/- 448.5 FT  
 DISCHARGE OVER ROAD @ Q100: N/A

UPSTREAM STRUCTURE

TOWN: ROCKINGHAM      DISTANCE: 0.5 MI  
 HIGHWAY #: T.H. # 3 (HARTLEY HILL ROAD)      STRUCTURE #: 9  
 CLEAR SPAN: 128 FT      CLEAR HEIGHT: 15.3 FT  
 YEAR BUILT: 2004      FULL WATERWAY: 2130 SF  
 STRUCTURE TYPE: WELDED PLATE GIRDER

DOWNSTREAM STRUCTURE

TOWN: ROCKINGHAM      DISTANCE: 1.0 MI  
 HIGHWAY #: T.H. # 51 (HALL BRIDGE ROAD)      STRUCTURE #: 43  
 CLEAR SPAN: 113      CLEAR HEIGHT: +/- 12 FT  
 YEAR BUILT: 1982      FULL WATERWAY: +/- 1350 SF

LRFR LOAD RATING FACTORS

LOADING LEVELS	TRUCK						
	H-20	HL-93	3S2	6 AXLE	3A. STR.	4A. STR.	5A. SEMI
TONNAGE	20	36	36	66	30	34.5	38
INVENTORY	4.136	1.187					
POSTING							
OPERATING	5.36	1.54	3.72	1.84	3.67	3.21	3.21
COMMENTS:							

PROPOSED STRUCTURE

STRUCTURE TYPE: 3 SPAN PRESTRESSED NEXT D BEAM BRIDGE

CLEAR SPAN (NORMAL TO STREAM): 170.21 FT  
 VERTICAL CLEARANCE ABOVE STREAMBED: 28.1 FT (AVG.)  
 WATERWAY OF FULL OPENING: 2460 SQ FT

WATER SURFACE ELEVATIONS AT: ONE BRIDGE LENGTH UPSTREAM

Q 2.33 = 428.7 FT      VELOCITY = 10.0 FT/SEC  
 Q 10 = 430.8 FT      "      11.1 FT/SEC  
 Q 25 = 432.6 FT      "      11.2 FT/SEC  
 Q50 = 433.9 FT      "      12.4 FT/SEC  
 Q 100 = 435.4 FT      "      13.6 FT/SEC

IS THE ROADWAY OVERTOPPED BELOW Q100? NO  
 FREQUENCY: >Q500  
 RELIEF ELEVATION: +/- 448.5 FT  
 DISCHARGE OVER ROAD @ Q100: N/A

AVERAGE LOW ELEVATION OF SUPERSTRUCTURE: 446.7  
 VERTICAL CLEARANCE: 12.8 FT @ Q50 = 8,680 CFS

SCOUR: CONTRACTION SCOUR FOR Q100 IS 2 FT (Q500 IS 3 FT) TOTAL PIER  
 SCOUR FOR Q100 IS 23 FT (Q500 IS 26 FT) STONE FILL, TYPE IV AT ABUTMENTS TO BE LEFT IN PLACE.  
 REQUIRED CHANNEL PROTECTION: EXISTING SCOUR CRITICAL PIERS RETAINED WITHOUT ADDED REVETMENT

PERMIT INFORMATION

AVERAGE DAILY FLOW: 150 CFS      DEPTH OR ELEVATION:  
 ORDINARY LOW WATER: 70 CFS      423.1 FT  
 ORDINARY HIGH WATER: 1230 CFS      426.6 FT

TEMPORARY BRIDGE REQUIREMENTS

STRUCTURE TYPE: N/A  
 CLEAR SPAN (NORMAL TO STREAM): N/A  
 VERTICAL CLEARANCE ABOVE STREAMBED: N/A  
 WATERWAY AREA OF FULL OPENING: N/A

ADDITIONAL INFORMATION

TRAFFIC MAINTENANCE NOTES

1. MAINTAIN SINGLE LANE ALTERNATING TRAFFIC USING PHASED CONSTRUCTION SEQUENCE
2. TEMPORARY TRAFFIC SIGNAL REQUIRED AT ROUTE 121 / OAK STREET INTERSECTION AND ON ROUTE 121 EASTERLY APPROACH

DESIGN VALUES


1. DESIGN LIVE LOAD: HL-93
2. FUTURE PAVEMENT:  $d_p$ : 3.0 INCH
3. ABUTMENT BEARING TO BEARING LENGTH (THREE SPANS):  $L$ : 200.00 FT (65.50 - 69.00 - 65.50) FT
4.  $\Delta$ :
5.  $f_y$ :
6.  $f_c$ :
7.  $f'c$ :
8. CONCRETE, HIGH PERFORMANCE CLASS AA:  $f_c$ : 4.0 KSI
9. CONCRETE, HIGH PERFORMANCE CLASS A:  $f_c$ : 4.0 KSI
10. CONCRETE, HIGH PERFORMANCE CLASS B:  $f_c$ : 3.5 KSI
11. CONCRETE, CLASS C:  $f_c$ :
12. REINFORCING STEEL:  $f_y$ : 60 KSI
13. STRUCTURAL STEEL AASHTO M270 (WEATHERING):  $f_y$ : 50 KSI
14. NOMINAL BEARING RESISTANCE OF SOIL:  $q_n$ :
15. SOIL BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD):  $\phi$ :
16. NOMINAL BEARING RESISTANCE OF ROCK:  $q_n$ :
17. ROCK BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD):  $\phi$ :
18. PILE RESISTANCE FACTOR:  $\phi$ : 0.65
19. LATERAL PILE DEFLECTION:  $\Delta$ : 0.066 INCH
20. BASIC WIND SPEED:  $V_{3s}$ : 50 MPH
21. MINIMUM GROUND SNOW LOAD:  $p_g$ :
22. SEISMIC DATA:  $PGA$ :  $S_s$ :  $S_1$ :

TRAFFIC DATA

YEAR	ADT	DHV	% D	% T	ADTT
2014	3700	420	55	7.0	280
2034	4000	450	55	9.5	410

20 year ESAL for flexible pavement from 2014 to 2034 : 1621000  
 40 year ESAL for flexible pavement from 2014 to 2054 : 3584000  
 Design Speed : 25 mph

TEMPORARY BRIDGE PROFILE ALONG TEMP CL



CALDERWOOD ENGINEERING, ETC.  
 STRUCTURAL ENGINEERING & DETAILING SERVICES  
 222 RIVER RD., RICHMOND, ME 04857 PH/FX (207)737-2007/(207) 737-2008  
 PREPARED FOR: COLD RIVER BRIDGES, LLC  
 CEE 106-BR-14

DATE	BY	REVISION	P.E. NUMBER	DATE
2014	ETC			
		DESIGN-DETAILED		
		CHECKED-REVIEWED		
		REVISIONS 1		
		REVISIONS 2		
		REVISIONS 3		
		REVISIONS 4		
		FIELD CHANGES		

VE SUPER. DESIGN  
 ROCKINGHAM VT. BR# 0126 (12)  
 PRELIMINARY INFORMATION SHEET

SHEET NUMBER  
 2

