

STATE OF VERMONT  
AGENCY OF TRANSPORTATION

ITEM DETAIL SUMMARY SHEET

BEGIN STATION	END STATION	POS.	203.30 EARTH BORROW	402.12 AGG. SHOULD.	507.12 RE- INFORCING STEEL, LEVEL II	525.10 REMOVAL OF EXIST. BRIDGE RAILING	525.50 BRIDGE RAILING REPAIR TYPE I	541.25 CONC. CLASS B	604.20 PRECAST CONC. CB W/CAST IRON GRATE	604.412 REHAB. D. I. CLASS I	613.10 STONE FILL, TYPE I	619.17 YIELD MARKER POSTS	621.20 STEEL BEAM G. R. GALV	621.205 STEEL BEAM G. R. GALV W/8' POSTS	621.21 HD STEEL BEAM G. R., GALV.	621.216 HD STEEL BEAM G. R., GALV./ NESTED W/8' POSTS	621.217 HD S. B. G. R., GALV./ NESTED W/8' POSTS	621.60 ANCHOR FOR S. B. G. R.	621.80 REMOVE & DISP. OF G. R.	649.31 GEOT. UNDER STONE FILL	651.35 TOPSOIL	651.40 GRUBBING MATERIAL	653.20 TEMP. EROSION MATTING	676.10 DEL. INE. WITH STEEL POSTS	676.12 REMOVAL OF EXIST. DEL. INE.	REMARKS		
			CY	TON	LBS	LF	LF	CY	EA	EACH	CY	EACH	LF	LF	LF	LF	LF	EACH	LF	SY	CY	SY	SY	EACH	EACH			
ELMORE																												
185+00	418+58	LT&RT		1135						4		80																
229+75	242+00	RT	50										329	900				2	1212.5						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 229+75 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 242+00	
239+25	243+75	LT	50										454					2	437.5						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 239+25 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 243+75	
295+72.5	298+10	RT	50											216.5			25	2	216						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 295+72.5 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 298+10	
295+97.5	298+35	LT	50										216.5			25		2	315						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 295+97.5 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 298+35	
299+00	309+00	LT	50											1004				2	950						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 299+00 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 309+00	
304+79.53	304+85.61	RT			376			2.05																			CONSTRUCT CONCRETE REINFORCED HEADWALL PER STD. D-33	
324+50	324+75	LT									4.0										17.5		7.8	17.5			PLACE STONE FILL ON SLOPES GREATER THAN 1:1.5 FOR SLOPE STABILIZATION	
357+69.5	359+69.5	LT	50			25	25						154		32.5			2	169						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 357+69.5 AND AT STA. 359+69.5	
358+40.5	360+15.5	RT	50			25	25						104		65			2	150						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. 358+40.5 AND AT STA. 360+15.5	
363+40	363+65	RT									4.5									19.0		9.3	19.0				PLACE STONE FILL ON SLOPES GREATER THAN 1:1.5 FOR SLOPE STABILIZATION	
MORRISTOWN																												
A 0+00	A 115+31.5	LT&RT		562						1		33														39.4		3
A 38+50		LT							1																		INSTALL NEW CB AT STA. A 38+71 LT AND EXTEND 18" RCP 3' LT	
A 52+40	A 52+50	LT									1.1										5.4		1.5	5.4			PLACE STONE FILL ON SLOPES GREATER THAN 1:1.5 FOR SLOPE STABILIZATION	
A 67+00	A 69+00	LT	50											204				2	191						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 67+00 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 69+00	
A 69+25	A 72+25	RT	50										127	177				2	234						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 69+25 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 72+25	
A 73+96	A 80+33.5	RT	50											641.5				2	628						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 73+96 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 80+33.5	
A 88+85	A 89+00	RT									1.6									8.2		2.3	8.2				PLACE STONE FILL ON SLOPES GREATER THAN 1:1.5 FOR SLOPE STABILIZATION	
A 109+00	A 111+75	LT	50											254			25	2	275						2	2	INSTALL 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 109+00 AND 12'-6" LONG, 16' RADIUS WITH ANCHOR AT STA. A 111+75	
SUBTOTAL			550	1697	376	50	50	2.05	1	5	11.2	113	1384.5	3397	97.5	25	50	22	4778	50.1	228.8	20.9	50.1	22	25			
ROUNDING			-	28	4	-	-	0.95	-	-	-	-	15.5	3	2.5	-	-	-	-	-	-	21.2	4.1	-	-			
TOTAL			550	1725	380	50	50	3	1	5	11.2	113	1400	3400	100	25	50	22	4778	50.1	250	25	50.1	22	25			

ITEM  
DETAIL  
SUMMARY  
SHEET

PROJECT NAME: ELMORE-MORRISTOWN  
PROJECT NUMBER: STP 2937 (1)  
FILE NAME: z11c310.dgn PLOT DATE: 3/3/14  
PROJECT LEADER: C. LATHROP DRAWN BY: S. LAMPHERE  
DESIGNED BY: S. LAMPHERE CHECKED BY: C. LATHROP  
PLOT FILE: z11c310\_17.i SHEET 17 OF 194