

NON STR. THK.	STRUCT. THK.	WEIGHT	WIDTH	HEIGHT	NO. REQ'D.	PANEL NUMBER OR TYPE
	42"	44.9 kips	9'-0"	11'-5 1/8"	1	ABUTMENT 1 RIGHT WINGWALL <i>REVISED 5/7/13</i>

P-52, 20-TON X 10" SWIFT-LIFT ANCHORS (2 REQUIRED)

14" WIDE x 6" DEEP SHEAR KEY

W B
F

VERIFY ALL DIMENSIONS PRIOR TO POURING PANEL

MINIMUM COMPRESSIVE STRENGTH REQ'D. = 4,000 PSI

CONSTRUCTION PERIOD: 72 mph

DESIGN WIND SPEED: 72 mph

TOTAL BRACE LOAD =

SCALE: RIGGING DETAILS

GROUND RELEASE II TILT-UP SYSTEM	X 4'-2 1/2"	ΔX -29 <	CY= 11.1	SCALE: RIGGING DETAILS
This drawing is furnished solely for the purpose of clarifying the proper use, installation and application of products supplied by Dayton Superior. Dayton Superior does not assume any responsibility for the correctness of structural designs or dimensions furnished by others. These drawings are intended merely to supplement the architectural and structural drawings and are to be used only in conjunction with them. In no way are these drawings to be interpreted as shop drawings for panel fabrication.	Y 4'-11 7/16"	ΔY -59	102.8	1/4"
PANEL VIEWED FROM:	ORDERED BY	DATE	JOB NO.	SHEET
INSIDE	BP	5/7/13	13200	2 of 3

NOTE: INSERT AND BRACING DESIGN SHOWN IS BASED ON THE USE OF DAYTON SUPERIOR PRODUCTS ONLY!