

NON STR. THK.	STRUCT. THK.	WEIGHT	WIDTH	HEIGHT	NO. REQ'D.	PANEL NUMBER OR TYPE
	42"	45.6 kips	8'-6"	12'-0 1/4"	1	ABUTMENT 2 RIGHT WINGWALL
<i>REVISED 5/7/13</i>						
<p>W B F VERIFY ALL DIMENSIONS PRIOR TO POURING PANEL. MINIMUM COMPRESSIVE STRENGTH REQ'D. = 4,000 PSI</p>						
Construction Period	Design Wind Speed	TOTAL BRACE LOAD =	B=	W=	F=	BRACE REQ'D.
72 mph						
<p>GROUND RELEASE II TILT-UP SYSTEM</p> <p>This drawing is furnished solely for the purpose of clarifying the proper use, installation and application of products supplied by Dayton Superior. Dayton Superior does not assume any responsibility for the correctness of structural designs or dimensions furnished by others. These drawings are intended merely to supplement the architectural and structural drawings and are to be used only in conjunction with them. In no way are these drawings to be interpreted as shop drawings for panel fabrication.</p>						
X	4'-0 5/16"	ΔX	-23 <	CY=	11.3	SCALE: RIGGING DETAILS
Y	5'-3 5/8"	ΔY	-45	GRADE AREA	102.2	1/4" R02
PANEL VIEWED FROM:			ORDERED BY	JOB NO.	SHEET	
INSIDE			BP	13200	4 of 18	
			DATE			
			5/7/13			
NOTE: INSERT AND BRACING DESIGN SHOWN IS BASED ON THE USE OF DAYTON SUPERIOR PRODUCTS ONLY!						