



50B COLTON LOAMY FINE SAND
WITH 2% TO 8% SLOPES
"K FACTOR" = 0.17

16B ADAMS LOAMY FINE SAND
WITH 2% TO 8% SLOPES
"K FACTOR" = 0.17

BENCHMARK
CHISELED SQUARE
IN TOP OF ABUT.
ELEV. 732.93

BENCHMARK
RR SPIKE IN POLE
ELEV. 728.63

BENCHMARK
RR SPIKE IN POLE
ELEV. 732.78

BENCHMARK
CHISELED SQUARE
ON ABUT.
ELEV. 731.75

BENCHMARK
STATE OF VERMONT
SURVEY DISK
ELEV. 733.77

61E HOUGHTONVILLE
FINE SANDY LOAM
WITH 25% TO 50% SLOPES
"K FACTOR" = 0.49

48D RAWSONVILLE-HOGBACK
FINE SANDY LOAM
WITH 15% TO 25% SLOPES
"K FACTOR" = 0.49

LEGEND

| | |
|--|-------------------|
| | RIPARIAN BUFFER |
| | P/L PROPERTY LINE |
| | RIGHT-OF-WAY LINE |
| | SOIL BOUNDARY |

EPSC EXISTING CONDITIONS SHEET I

SCALE 1" = 20'-0"
20 0 20

| | | | |
|-----------------|---------------------|----------------------------------|----------------|
| PROJECT NAME: | JAMAICA | PLOT DATE: | 07-DEC-2012 |
| PROJECT NUMBER: | ER-BRF 015-I(23) | PROJECT LEADER: | K. HIGGINS |
| FILE NAME: | s11b316.epsc.ex.dgn | DESIGNED BY: | K. FRIEDLAND |
| | | CHECKED BY: | G. LAROCHE |
| | | EPSC EXISTING CONDITIONS SHEET I | SHEET 45 OF 82 |