



### Specifications

Item	Description
Voltage and Amperage	12-74VDC draws 1.25A @ 12V tapering to 0.2A average @ 74V 120VAC draws 0.3A average 240VAC draws 0.3A average
Power Supply Output	11 Watts
Flash Rate	8 joules per flash
Flash Rate	80 to 95 flashes per minute
Size and Weight	6.75" tall x 5.5" dia. x 2.2 lbs ( 171mm x 140mm x 1.0kg )

### Available Options

NOTE: All "/" options are factory installed only.

Model No.	Description
BKT	Mounting bracket
/LBO-MAXI	Lens blackout segment 180°
800/1250-DC	Clear lens dust cover
G800	Heavy duty guard
TBO-MAXI	Top lens blackout
800-FLG	Chrome flange mounting ring ( standard on DC versions, optional on AC versions )

### Replacement Parts

Model No.	Description
4001	Xenon strobe lamp
1700	Color lens ( please specify color ) - RED ←
801-110-BASE	120VAC power supply
801LC-BASE	120VAC power supply with AC cord set
801MBSC-BASE	120VAC power supply with magnetic mount and straight cord
801-240-BASE	240VAC power supply
801-1274-BASE	12-74VDC power supply
801MB-BASE	12-74VDC power supply with magnetic mount and coil cord