

PRELIMINARY INFORMATION SHEET (CULVERT)

LRFD

INDEX OF SHEETS						FINAL HYDRAULIC REPORT																																																																																											
PLAN SHEETS						STANDARDS LIST						HYDROLOGIC DATA						PROPOSED STRUCTURE																																																																															
SEE SHEET 2 FOR INDEX OF SHEETS AND STANDARDS LIST						<p>DATE: APRIL 2012</p> <p>DRAINAGE AREA: 1.2 Sq. Miles</p> <p>CHARACTER OF TERRAIN: Hilly - mostly forest</p> <p>STREAM CHARACTERISTICS: Narrow and curving with small current</p> <p>NATURE OF STREAMBED: Mostly gravel and cobbles</p> <p>PEAK FLOW DATA</p> <table border="0"> <tr> <td>Q 2.33 = 70 cfs</td> <td>Q 50 = 200 cfs</td> </tr> <tr> <td>Q 10 = 140 cfs</td> <td>Q 100 = 220 cfs</td> </tr> <tr> <td>Q 25 = 170 cfs</td> <td>Q 500 = 280 cfs</td> </tr> </table> <p>ESTIMATED DISCHARGE: Unknown</p> <p>DATE OF FLOOD OF RECORD: NOV 1927 and Aug, 2011</p> <p>WATER SURFACE ELEV.: _____</p> <p>NATURAL STREAM VELOCITY: @ Q50 = Unknown</p> <p>ICE CONDITIONS: Light</p> <p>DEBRIS: Moderate</p> <p>DOES THE STREAM REACH MAXIMUM HIGHWATER ELEV. RAPIDLY? Yes</p> <p>IS ORDINARY RISE RAPID? Yes</p> <p>IS STAGE AFFECTED BY UPSTREAM OR DOWNSTREAM CONDITIONS? No</p> <p>IF YES, DESCRIBE: _____</p> <p>WATERSHED STORAGE: < 1% HEADWATERS: _____</p> <p>UNIFORM: X</p> <p>IMMEDIATELY ABOVE SITE: _____</p> <p>EXISTING STRUCTURE INFORMATION</p> <p>STRUCTURE TYPE: Three sided concrete frame 8 ft x 4 ft</p> <p>YEAR BUILT: 1957 - Undermined Aug 2011</p> <p>CLEAR SPAN(NORMAL TO STREAM): 8 Foot Diameter</p> <p>VERTICAL CLEARANCE ABOVE STREAMBED: 4 feet</p> <p>WATERWAY OF FULL OPENING: Approx. 32 Sq. Feet</p> <p>DISPOSITION OF STRUCTURE: Removed by VTrans Fall 2011</p> <p>TYPE OF MATERIAL UNDER SUBSTRUCTURE: Gravel and sand</p> <p>WATER SURFACE ELEVATIONS AT:</p> <table border="0"> <tr> <td>Q2.33 = _____</td> <td>VELOCITY = _____</td> </tr> <tr> <td>Q10 = _____</td> <td>" " _____</td> </tr> <tr> <td>Q25 = _____</td> <td>" " _____</td> </tr> <tr> <td>Q50 = _____</td> <td>" " _____</td> </tr> <tr> <td>Q100 = _____</td> <td>" " _____</td> </tr> </table> <p>LONG TERM STREAMBED CHANGES: _____</p> <p>IS THE ROADWAY OVERTOPPED BELOW Q100: No</p> <p>FREQUENCY: _____</p> <p>RELIEF ELEVATION: _____</p> <p>DISCHARGE OVER ROAD @Q100: _____</p> <p>UPSTREAM STRUCTURE</p> <p>TOWN: None DISTANCE: _____</p> <p>HIGHWAY #: _____ STRUCTURE #: _____</p> <p>CLEAR SPAN: _____ CLEAR HEIGHT: _____</p> <p>YEAR BUILT: _____ FULL WATERWAY: _____</p> <p>STRUCTURE TYPE: _____</p> <p>DOWNSTREAM STRUCTURE</p> <p>TOWN: Beebe Pond DISTANCE: 350 ft</p> <p>HIGHWAY #: _____ STRUCTURE #: _____</p> <p>CLEAR SPAN: _____ CLEAR HEIGHT: _____</p> <p>YEAR BUILT: _____ FULL WATERWAY: _____</p> <p>STRUCTURE TYPE: _____</p>						Q 2.33 = 70 cfs	Q 50 = 200 cfs	Q 10 = 140 cfs	Q 100 = 220 cfs	Q 25 = 170 cfs	Q 500 = 280 cfs	Q2.33 = _____	VELOCITY = _____	Q10 = _____	" " _____	Q25 = _____	" " _____	Q50 = _____	" " _____	Q100 = _____	" " _____	<p>STRUCTURE TYPE: BOX CULVERT</p> <p>CLEAR SPAN(NORMAL TO STREAM): 14 Feet</p> <p>VERTICAL CLEARANCE ABOVE STREAMBED: 5 Feet</p> <p>WATERWAY OF FULL OPENING: 70 Sq. Feet</p> <p>WATER SURFACE ELEVATIONS AT:</p> <table border="0"> <tr> <td>Q2.33 = 624.7</td> <td>VELOCITY = 3.1 FT/SEC</td> </tr> <tr> <td>Q10 = 626.3</td> <td>" 4.7 FT/SEC</td> </tr> <tr> <td>Q25 = 628.8</td> <td>" 5.3 FT/SEC</td> </tr> <tr> <td>Q50 = 627.3</td> <td>" 6.3 FT/SEC</td> </tr> <tr> <td>Q100 = 627.6 Feet</td> <td>" 6.9 FT/SEC</td> </tr> </table> <p>IS THE ROADWAY OVERTOPPED BELOW Q100: No</p> <p>FREQUENCY: _____</p> <p>RELIEF ELEVATION: _____</p> <p>DISCHARGE OVER ROAD @Q100: No</p> <p>AVERAGE LOW ELEVATION OF SUPERSTRUCTURE: 628.0</p> <p>VERTICAL CLEARANCE: @ Q 50 = 0.7 FT @ Q 100 = 0.4 FT</p> <p>SCOUR: _____</p> <p>REQUIRED CHANNEL PROTECTION: Type II Stone Fill</p> <p>PERMIT INFORMATION</p> <p>AVERAGE DAILY FLOW: 3 CFS DEPTH OR ELEVATION: _____</p> <p>ORDINARY LOW WATER: 1 CFS 0.2 FEET</p> <p>ORDINARY HIGH WATER: 70 CFS 2.0 FEET</p> <p>TEMPORARY BRIDGE REQUIREMENTS</p> <p>STRUCTURE TYPE: N/A - VT 30 to be closed</p> <p>CLEAR SPAN (NORMAL TO STREAM): _____</p> <p>VERTICAL CLEARANCE ABOVE STREAMBED: _____</p> <p>WATERWAY AREA OF FULL OPENING: _____</p> <p>ADDITIONAL INFORMATION</p> <p>Existing two 48 in x 40 ft HDPE temporary pipes, installed in Fall of 2011 by VTrans are to be removed and retained by contractor.</p> <p>TRAFFIC MAINTENANCE NOTES</p> <ol style="list-style-type: none"> 1. MAINTAIN TRAFFIC ON AN OFF SITE DETOUR. 2. TRAFFIC SIGNALS ARE NOT NECESSARY. 3. SIDEWALKS ARE NOT NECESSARY. <p>DESIGN VALUES</p> <table border="0"> <tr> <td>1. DESIGN LIVE LOAD</td> <td>HL-93</td> </tr> <tr> <td>2. FUTURE PAVEMENT</td> <td>d_p: 3.0 INCH</td> </tr> <tr> <td>3. CULVERT OPENING</td> <td>D: 14 FT FT</td> </tr> <tr> <td>4. MIN. MID-SPAN POS. CAMBER @ RELEASE (PRESTRESSED UNITS)</td> <td>Δ: ---</td> </tr> <tr> <td>5. PRESTRESSING STRAND</td> <td>f_y: ---</td> </tr> <tr> <td>6. PRESTRESSED CONCRETE STRENGTH</td> <td>f'c: ---</td> </tr> <tr> <td>7. PRESTRESSED CONCRETE RELEASE STRENGTH</td> <td>f'el: ---</td> </tr> <tr> <td>8. CONCRETE, HIGH PERFORMANCE CLASS AA</td> <td>f'c: ---</td> </tr> <tr> <td>9. CONCRETE, HIGH PERFORMANCE CLASS A</td> <td>f'c: ---</td> </tr> <tr> <td>10. CONCRETE, HIGH PERFORMANCE CLASS B</td> <td>f'c: ---</td> </tr> <tr> <td>11. CONCRETE, CLASS C</td> <td>f'c: ---</td> </tr> <tr> <td>12. REINFORCING STEEL</td> <td>f_y: 60 KSI</td> </tr> <tr> <td>13. STRUCTURAL STEEL AASHTO M270</td> <td>f_y: ---</td> </tr> <tr> <td>14. SOIL UNIT WEIGHT</td> <td>γ: 0.130 KCF</td> </tr> <tr> <td>15. NOMINAL BEARING RESISTANCE OF SOIL</td> <td>q_n: 2.5 KSF</td> </tr> <tr> <td>16. SOIL BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)</td> <td>φ: 1.00</td> </tr> <tr> <td>17. NOMINAL BEARING RESISTANCE OF ROCK</td> <td>q_n: ---</td> </tr> <tr> <td>18. ROCK BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)</td> <td>φ: ---</td> </tr> <tr> <td>19. NOMINAL AXIAL PILE RESISTANCE</td> <td>q_p: ---</td> </tr> <tr> <td>20. PILE YIELD STRENGTH ASTM A572</td> <td>f_y: ---</td> </tr> <tr> <td>21. PILE SIZE</td> <td>---</td> </tr> <tr> <td>22. EST. PILE LENGTH</td> <td>L_p: ---</td> </tr> <tr> <td>23. PILE RESISTANCE FACTOR</td> <td>φ: ---</td> </tr> <tr> <td>24. LATERAL PILE DEFLECTION</td> <td>Δ: ---</td> </tr> <tr> <td>25. BASIC WIND SPEED</td> <td>V_{3s}: ---</td> </tr> <tr> <td>26. MINIMUM GROUND SNOW LOAD</td> <td>p_g: ---</td> </tr> <tr> <td>27. SEISMIC DATA</td> <td>PGA: --- S: --- S_f: ---</td> </tr> </table>						Q2.33 = 624.7	VELOCITY = 3.1 FT/SEC	Q10 = 626.3	" 4.7 FT/SEC	Q25 = 628.8	" 5.3 FT/SEC	Q50 = 627.3	" 6.3 FT/SEC	Q100 = 627.6 Feet	" 6.9 FT/SEC	1. DESIGN LIVE LOAD	HL-93	2. FUTURE PAVEMENT	d _p : 3.0 INCH	3. CULVERT OPENING	D: 14 FT FT	4. MIN. MID-SPAN POS. CAMBER @ RELEASE (PRESTRESSED UNITS)	Δ: ---	5. PRESTRESSING STRAND	f _y : ---	6. PRESTRESSED CONCRETE STRENGTH	f'c: ---	7. PRESTRESSED CONCRETE RELEASE STRENGTH	f'el: ---	8. CONCRETE, HIGH PERFORMANCE CLASS AA	f'c: ---	9. CONCRETE, HIGH PERFORMANCE CLASS A	f'c: ---	10. CONCRETE, HIGH PERFORMANCE CLASS B	f'c: ---	11. CONCRETE, CLASS C	f'c: ---	12. REINFORCING STEEL	f _y : 60 KSI	13. STRUCTURAL STEEL AASHTO M270	f _y : ---	14. SOIL UNIT WEIGHT	γ: 0.130 KCF	15. NOMINAL BEARING RESISTANCE OF SOIL	q _n : 2.5 KSF	16. SOIL BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)	φ: 1.00	17. NOMINAL BEARING RESISTANCE OF ROCK	q _n : ---	18. ROCK BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)	φ: ---	19. NOMINAL AXIAL PILE RESISTANCE	q _p : ---	20. PILE YIELD STRENGTH ASTM A572	f _y : ---	21. PILE SIZE	---	22. EST. PILE LENGTH	L _p : ---	23. PILE RESISTANCE FACTOR	φ: ---	24. LATERAL PILE DEFLECTION	Δ: ---	25. BASIC WIND SPEED	V _{3s} : ---	26. MINIMUM GROUND SNOW LOAD	p _g : ---	27. SEISMIC DATA	PGA: --- S: --- S _f : ---
Q 2.33 = 70 cfs	Q 50 = 200 cfs																																																																																																
Q 10 = 140 cfs	Q 100 = 220 cfs																																																																																																
Q 25 = 170 cfs	Q 500 = 280 cfs																																																																																																
Q2.33 = _____	VELOCITY = _____																																																																																																
Q10 = _____	" " _____																																																																																																
Q25 = _____	" " _____																																																																																																
Q50 = _____	" " _____																																																																																																
Q100 = _____	" " _____																																																																																																
Q2.33 = 624.7	VELOCITY = 3.1 FT/SEC																																																																																																
Q10 = 626.3	" 4.7 FT/SEC																																																																																																
Q25 = 628.8	" 5.3 FT/SEC																																																																																																
Q50 = 627.3	" 6.3 FT/SEC																																																																																																
Q100 = 627.6 Feet	" 6.9 FT/SEC																																																																																																
1. DESIGN LIVE LOAD	HL-93																																																																																																
2. FUTURE PAVEMENT	d _p : 3.0 INCH																																																																																																
3. CULVERT OPENING	D: 14 FT FT																																																																																																
4. MIN. MID-SPAN POS. CAMBER @ RELEASE (PRESTRESSED UNITS)	Δ: ---																																																																																																
5. PRESTRESSING STRAND	f _y : ---																																																																																																
6. PRESTRESSED CONCRETE STRENGTH	f'c: ---																																																																																																
7. PRESTRESSED CONCRETE RELEASE STRENGTH	f'el: ---																																																																																																
8. CONCRETE, HIGH PERFORMANCE CLASS AA	f'c: ---																																																																																																
9. CONCRETE, HIGH PERFORMANCE CLASS A	f'c: ---																																																																																																
10. CONCRETE, HIGH PERFORMANCE CLASS B	f'c: ---																																																																																																
11. CONCRETE, CLASS C	f'c: ---																																																																																																
12. REINFORCING STEEL	f _y : 60 KSI																																																																																																
13. STRUCTURAL STEEL AASHTO M270	f _y : ---																																																																																																
14. SOIL UNIT WEIGHT	γ: 0.130 KCF																																																																																																
15. NOMINAL BEARING RESISTANCE OF SOIL	q _n : 2.5 KSF																																																																																																
16. SOIL BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)	φ: 1.00																																																																																																
17. NOMINAL BEARING RESISTANCE OF ROCK	q _n : ---																																																																																																
18. ROCK BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)	φ: ---																																																																																																
19. NOMINAL AXIAL PILE RESISTANCE	q _p : ---																																																																																																
20. PILE YIELD STRENGTH ASTM A572	f _y : ---																																																																																																
21. PILE SIZE	---																																																																																																
22. EST. PILE LENGTH	L _p : ---																																																																																																
23. PILE RESISTANCE FACTOR	φ: ---																																																																																																
24. LATERAL PILE DEFLECTION	Δ: ---																																																																																																
25. BASIC WIND SPEED	V _{3s} : ---																																																																																																
26. MINIMUM GROUND SNOW LOAD	p _g : ---																																																																																																
27. SEISMIC DATA	PGA: --- S: --- S _f : ---																																																																																																
TRAFFIC DATA						LRFR LOAD RATING FACTORS						CULVERT DESIGN CRITERIA																																																																																					
YEAR	ADT	DHV	% D	% T	ADTT	LOADING LEVELS	TRUCK							<p>1. CULVERT WILL BE SET AT A SLOPE OF 0.006 FT/FT</p> <p>2. CULVERT WILL NOT REQUIRE FISH PASSAGE ACCOMODATIONS</p> <p>3. CULVERT CONSTRUCTION WILL NOT REQUIRE A TEMPORARY PIPE OR PUMPING</p>																																																																																			
2012	1500	190	50	6.4	100	H-20	HL-93	3S2	6 AXLE	3A STR.	4A STR.	5A SEMI																																																																																					
2032	1800	210	50	6.4	120	TONNAGE	20	36	36	66	30	34.5	38																																																																																				
						INVENTORY																																																																																											
						POSTING																																																																																											
						OPERATING																																																																																											
						COMMENTS:	TABLE TO BE COMPLETED BY CONTRACTOR'S DESIGNER																																																																																										
AS BUILT "REBAR" DETAILS						CULVERT DESIGN CRITERIA						PROJECT INFORMATION																																																																																					
LEVEL I		LEVEL II		LEVEL III		<p>1. CULVERT WILL BE SET AT A SLOPE OF 0.006 FT/FT</p> <p>2. CULVERT WILL NOT REQUIRE FISH PASSAGE ACCOMODATIONS</p> <p>3. CULVERT CONSTRUCTION WILL NOT REQUIRE A TEMPORARY PIPE OR PUMPING</p>						PROJECT NAME: HUBBARDTON																																																																																					
TYPE:	TYPE:	TYPE:	PROJECT NUMBER: ER STP 0161(27)																																																																																														
GRADE:	GRADE:	GRADE:	FILE NAME: z11c290pl.xls PLOT DATE: 7/16/2012																																																																																														
						<p>DESIGNED BY: S.G. FARNSWORTH</p> <p>PRELIMINARY INFORMATION SHEET</p>						<p>PROJECT LEADER: M.A. COLGAN DRAWN BY: C.L. CILLEY</p> <p>CHECKED BY: S.G. FARNSWORTH</p> <p>SHEET 42 OF 70</p>																																																																																					

FABRICATOR RESPONSIBLE FOR LOAD RATING

