

ANALYSIS OF VALMONT INDUSTRIES LIGHTING STRUCTURE
IN ACCORDANCE WITH AASHTO-2009 RQMTS. (FINAL DEFLECTED POSITION)
BY BNS 5/12/2014 VERSION Fuse 1.10.0.540 32-bit

SUBJECT: VERMONT, 42' MAST ARM & 16' LUM ARM

FOLDER: VTTRAF FILE: 4216

BASE PLATE (SQUARE)

=====

WIDTH	=	20.00 IN
THICKNESS	=	1.500 IN
YIELD STRENGTH	=	36 KSI
STATIC COMBINED STRESS RATIO	=	0.56
BASE WELD TYPE	=	FULL-PEN

ANALYSIS OF BASE PLATE

=====

COMBINED STRESS RATIO	=	0.56
GROUP LOAD NUMBER	=	3
CRITICAL WIND DIRECT.*	=	70.00 DEGREES
ALIGNMENT OF THE BEND LINE	=	315.00 DEGREES
BOLT FORCE	=	38337 LBS
BOLT-TO-BEND LINE MOMENT ARM	=	3.00 IN
WIDTH OF BENDING SECTION	=	15.28 IN
APPLIED BENDING STRESS	=	20.07 KSI
ALLOWABLE BENDING STRESS	=	35.91 KSI

ANCHOR BOLTS

=====

QUANTITY	=	4
BOLT DIAMETER	=	1.50 IN
BOLT CIRCLE	=	19.00 IN
INITIAL BOLT ANGLE	=	45.00 DEGREES
BOLT LENGTH	=	54 IN
YIELD STRENGTH	=	55.00 KSI
STATIC COMBINED STRESS RATIO	=	0.62
FATIGUE STRESS RATIO	=	0.43