



GENERAL NOTES
 1. ALL WORK AND MATERIALS SHALL CONFORM TO THE STATE OF VERMONT, DEPARTMENT OF HIGHWAYS, STANDARD SPECIFICATIONS FOR HIGHWAY AND BRIDGE CONSTRUCTION DATED APRIL 1964, AND THE A.A.S.H.O. SPECIFICATIONS DATED 1961. DESIGNED FOR HS20-44 LOADING.
 2. ALL REINFORCING STEEL SHALL BE DETAILED ON THE REINFORCING STEEL SCHEDULE. ALL SPLICES SHALL BE A MINIMUM OF 40 BAR DIAMETERS.

FAIR HAVEN - WEST RUTLAND
 BF MEMB (35)
 SHEET 44 OF 44
 BRIDGE NO. 15E
 FOR REFERENCE ONLY

SUMMARY OF QUANTITIES

ITEM NO.	ITEM	UNIT	TOTAL	FINAL
318	TAR EMULSION FOR BRIDGE FLOORS	GAL.		
361	BITUMINOUS CONCRETE PAVEMENT MOD.	TONS		
372-A	JOINT SEALER - HOT Poured	L.F.		
372-C	JOINT SEALER - PREFORMED, TYPE A	L.F.		
372-C	JOINT SEALER - PREFORMED, TYPE B	L.F.		
401-B	CONCRETE CLASS B	CY.		
402	REINFORCING STEEL	LB.		

REINFORCING BENDING DETAILS

REINFORCING STEEL

BAR NO.	NO. PIECES	LENGTH	WEIGHT PER FT.	WEIGHT IN LBS.
AS 1			4.303	
AS 2			4.303	
AS 3			1.043	
AS 4			1.043	

TOTAL WEIGHT =

REVISIONS AND CORRECTIONS
 1. DIMENSIONS OF JOINT FOR SEALER TYPE A REVISED, 4/15/65 W.B.T.
 2. DIMENSIONS OF JOINT SEALER TYPE B REVISED AND MODIFICATION OF ITEM 372-C ADDED, 6/25/65 W.B.T.

DRAWN BY: W.B.T. Jan. 1965
 TRACED BY: W.B.T. Jan. 1965
 CHECKED BY: W.M.S. Feb. 1965

RECOMMENDED FOR APPROVAL: [Signature] 2/4/65
 BRIDGE ENGINEER DATE
 RECOMMENDED FOR APPROVAL: [Signature] 2/4/65
 ASSISTANT CHIEF ENGINEER DATE
 APPROVED BY: [Signature] 2/4/65
 CHIEF ENGINEER DATE

DETAILS OF APPROACH SLAB
 FOR 38' FOOT BRIDGE
 (WIDTH)
 TO BE USED FOR BRIDGE AT STATION 774+50
 LOCATION APPROACH SLAB NO. 4 (E.B.)

STATE OF VERMONT
 DEPARTMENT OF HIGHWAYS
 STANDARD STRUCTURE
 SB-AS-65

TOWN OF FAIR HAVEN - WEST RUTLAND
 ROUTE NO. RELOC. U.S. 4
 STA. 774+50 ±
 DESIGNED BY J. WOOD CHECKED BY D. SAAL
 PROJECT NO. AP-020-1(10) 12-65
 BR 313 OF 315 SHEET 156 OF 359