

# PRELIMINARY INFORMATION SHEET (CULVERT)

INDEX OF SHEETS

FINAL HYDRAULIC REPORT

PLAN SHEETS

1	TITLE SHEET
2	PRELIMINARY INFORMATION SHEET
3	CONVENTIONAL SYMBOLOLOGY LEGEND SHEET
4	TYPICAL SECTIONS SHEET
5	PROJECT NOTES SHEET
6	DETAIL SHEET
7	LANDSCAPE DETAILS SHEET
8 - 9	TIE SHEETS
10	CHANNEL ALIGNMENT SHEET
11 - 12	BORING SHEETS
13 - 14	QUANTITY SHEETS
15	R.O.W. DETAIL SHEET
16	R.O.W. LAYOUT SHEET
17	PLAN SHEET
18	ACCESS ROAD PLAN SHEET
19	ACCESS ROAD PROFILE SHEET
20	LANDSCAPE PLAN SHEET
21	EPSC NARRATIVE SHEET
22 - 23	EPSC DETAIL SHEETS
24	EPSC PLAN SHEET
25 - 28	VT 78 CROSS SECTION SHEETS
29 - 31	NORTH ACCESS RD CROSS SECTION SHEETS
32 - 33	SOUTH ACCESS RD CROSS SECTION SHEETS
34 - 39	CHANNEL CROSS SECTION SHEETS
40	CONSTRUCTION APPROACH SIGNING SHEET

STANDARDS LIST

G-1	11-10-2015
T-1	04-25-2016
T-10	08-06-2012
T-28	08-06-2012
T-29	08-06-2012
T-30	08-06-2012
T-42	04-09-2014
T-45	01-02-2013

STRUCTURES DETAIL SHEETS

SD-501.00	CONCRETE DETAILS AND NOTES	5/7/2010
SD-502.00	CONCRETE DETAILS AND NOTES	5/7/2010

HYDROLOGIC DATA

Date: March 2015

DRAINAGE AREA : 0.34 sq. mi.  
 CHARACTER OF TERRAIN : Hilly, mixture of open and forested land cover  
 STREAM CHARACTERISTICS : Sinuous, alluvial, low grade upstream & steep downstream  
 NATURE OF STREAMBED : Silt & sand upstream, stone, gravel, silt & sand downstream

PEAK FLOW DATA

Q 2.33 =	45 cfs	Q 50 =	120 cfs
Q 10 =	80 cfs	Q 100 =	140 cfs
Q 25 =	100 cfs	Q 500 =	190 cfs

DATE OF FLOOD OF RECORD : Unknown  
 ESTIMATED DISCHARGE : Unknown  
 WATER SURFACE ELEV. : Unknown  
 NATURAL STREAM VELOCITY : @ Q50 = 13.3 fps  
 ICE CONDITIONS : Light to moderate  
 DEBRIS : Moderate to heavy  
 DOES THE STREAM REACH MAXIMUM HIGHWATER ELEV. RAPIDLY? : Yes  
 IS ORDINARY RISE RAPID? : Yes  
 IS STAGE AFFECTED BY UPSTREAM OR DOWNSTREAM CONDITIONS? : No  
 IF YES, DESCRIBE :

WATERSHED STORAGE : < 1% HEADWATERS :  
 UNIFORM : X  
 IMMEDIATELY ABOVE SITE :

EXISTING STRUCTURE INFORMATION

STRUCTURE TYPE : Reinforced Concrete Box  
 YEAR BUILT : Unknown  
 CLEAR SPAN(NORMAL TO STREAM) : 4.0'  
 VERTICAL CLEARANCE ABOVE STREAMBED : 4.0'  
 WATERWAY OF FULL OPENING : 16 sq. ft.  
 DISPOSITION OF STRUCTURE : Abandon and fill with flowable fill  
 TYPE OF MATERIAL UNDER SUBSTRUCTURE : See boring logs

WATER SURFACE ELEVATIONS AT:

Q2.33 =	259.5'	VELOCITY =	11.2 fps
Q10 =	260.7'	"	12.9 fps
Q25 =	261.3'	"	13.6 fps
Q50 =	262.0'	"	14.2 fps
Q100 =	262.7'	"	14.7 fps

LONG TERM STREAMBED CHANGES : The only changes noted are deposition upstream and erosion downstream, likely due to the inadequate size and failure of the existing structure.

IS THE ROADWAY OVERTOPPED BELOW Q100 : No  
 FREQUENCY : Above Q100  
 RELIEF ELEVATION : 285.0'  
 DISCHARGE OVER ROAD @Q100 : None

UPSTREAM STRUCTURE

TOWN : None DISTANCE :  
 HIGHWAY # : STRUCTURE # :  
 CLEAR SPAN : CLEAR HEIGHT :  
 YEAR BUILT : FULL WATERWAY :  
 STRUCTURE TYPE :

DOWNSTREAM STRUCTURE

TOWN : Highgate DISTANCE : 800'  
 HIGHWAY # : Rail trail STRUCTURE # : -  
 CLEAR SPAN : Unknown CLEAR HEIGHT : Unknown  
 YEAR BUILT : Unknown FULL WATERWAY : -  
 STRUCTURE TYPE : Unknown

LRFR LOAD RATING FACTORS

LOADING LEVELS	TRUCK						
	H-20	HL-93	3S2	6 AXLE	3A STR.	4A STR.	5A SEM
TONNAGE	20	36	36	66	30	34.5	38
INVENTORY							
POSTING							
OPERATING							
COMMENTS:	TABLE TO BE COMPLETED BY CONTRACTOR'S DESIGNER						

AS BUILT "REBAR" DETAIL

AS BUILT "REBAR" DETAIL		
LEVEL I	LEVEL II	LEVEL III
TYPE:	TYPE:	TYPE:
GRADE:	GRADE:	GRADE:

CULVERT DESIGN CRITERIA

- PROPOSED CULVERT IS A STEEL CORRUGATED (6'-0" X 6'-0" X 131'-0" PIPE).
- CULVERT ENDS ARE NOT SKEWED.
- CULVERT WILL BE SET AT A SLOPE OF 12.00 IN. ON 50 FT.
- CULVERT WILL NOT REQUIRE FISH PASSAGE ACCOMMODATIONS
- CULVERT CONSTRUCTION WILL NOT REQUIRE A TEMPORARY PIPE

TRAFFIC DATA

YEAR	ADT	DHV	% D	% T	ADTT	
0	0	0	0	0	0	20 year ESAL for flexible pavement from XXXX to XXXX : 0
XXXX	0	0	0	0	0	40 year ESAL for flexible pavement from XXXX to XXXX : 0
						Design Speed : 0 mph

PROPOSED STRUCTURE

STRUCTURE TYPE : Smooth interior steel pipe with cement mortar lining  
 CLEAR SPAN(NORMAL TO STREAM) : 5.9'  
 VERTICAL CLEARANCE ABOVE STREAMBED : 5.9'  
 WATERWAY OF FULL OPENING : 27 sq. ft.

WATER SURFACE ELEVATIONS AT:

Q2.33 =	259.1'	VELOCITY=	13.0 fps
Q10 =	260.1'	"	14.6 fps
Q25 =	260.6'	"	15.2 fps
Q50 =	261.0'	"	15.7 fps
Q100 =	261.5'	"	16.2 fps

IS THE ROADWAY OVERTOPPED BELOW Q100 : No  
 FREQUENCY : Above Q100  
 RELIEF ELEVATION : 285.0'  
 DISCHARGE OVER ROAD @Q100 : None

AVERAGE LOW ELEVATION OF SUPERSTRUCTURE : 262.6' (top of pipe at inlet)  
 VERTICAL CLEARANCE : @ Q50 = 1.6'

SCOUR : Not applicable for a pipe

REQUIRED CHANNEL PROTECTION : Stone Fill, Type II at inlet and Type IV at outlet

PERMIT INFORMATION

AVERAGE DAILY FLOW : 1 cfs DEPTH OR ELEVATION :  
 ORDINARY LOW WATER : 0.5 cfs Depth < 0.5'  
 ORDINARY HIGH WATER : 20 cfs Depth = 2'

TEMPORARY BRIDGE REQUIREMENTS

STRUCTURE TYPE : No temporary structure required  
 CLEAR SPAN (NORMAL TO STREAM) :  
 VERTICAL CLEARANCE ABOVE STREAMBED :  
 WATERWAY AREA OF FULL OPENING :

ADDITIONAL INFORMATION

TRAFFIC MAINTENANCE NOTES

- MAINTAIN TWO-WAY TRAFFIC ON THE EXISTING STRUCTURE.
- TRAFFIC SIGNALS ARE NOT NECESSARY.
- SIDEWALKS ARE NOT NECESSARY

DESIGN VALUES

1. DESIGN LIVE LOAD	HL-93
2. FUTURE PAVEMENT	d <sub>p</sub> : 3.0 INCH
3. CULVERT OPENING	D: 6.00 FT
4. MIN. MID-SPAN POS. CAMBER @ RELEASE (PRESTRESSED UNITS)	Δ: ---
5. PRESTRESSING STRAND	f <sub>y</sub> : ---
6. PRESTRESSED CONCRETE STRENGTH	f' <sub>c</sub> : ---
7. PRESTRESSED CONCRETE RELEASE STRENGTH	f' <sub>cr</sub> : ---
8. CONCRETE, HIGH PERFORMANCE CLASS AA	f' <sub>c</sub> : 4.0 KSI
9. CONCRETE, HIGH PERFORMANCE CLASS A	f' <sub>c</sub> : 4.0 KSI
10. CONCRETE, HIGH PERFORMANCE CLASS B	f' <sub>c</sub> : 3.5 KSI
11. CONCRETE, CLASS C	f' <sub>c</sub> : 3.0 KSI
12. REINFORCING STEEL	f <sub>y</sub> : 60 KSI
13. STRUCTURAL STEEL AASHTO M270	f <sub>y</sub> : ---
14. NOMINAL BEARING RESISTANCE OF SOIL	q <sub>n</sub> : ---
15. SOIL BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)	φ: 0.45
16. NOMINAL BEARING RESISTANCE OF ROCK	q <sub>n</sub> : 10.0 KSF
17. ROCK BEARING RESISTANCE FACTOR (REFER TO AASHTO LRFD)	φ: 0.45
18. PILE RESISTANCE FACTOR	φ: ---
19. LATERAL PILE DEFLECTION	Δ: ---
20. BASIC WIND SPEED	V <sub>3s</sub> : ---
21. MINIMUM GROUND SNOW LOAD	p <sub>g</sub> : ---
22. SEISMIC DATA	PGA: 0 S: --- S <sub>i</sub> : ---
23.	---
24.	---
25.	---
26.	---

PROJECT NAME : HIGHGATE  
 PROJECT NUMBER : STP SCR(12)  
 FILE NAME : d13c134\_P1.xls PLOT DATE : 10/13/2016  
 PROJECT LEADER : B. MARTIN DRAWN BY : A. KEMPTON  
 DESIGNED BY : A. KEMPTON CHECKED BY : D. WILLEY  
 PRELIMINARY INFORMATION SHEET 1 SHEET 2 OF 40