


SEE BELOW



SEE NEXT SHEET

SUPERELEVATION BANKING NOTES:

1. SUPERELEVATION RATES AND RUNOFF LENGTHS WERE DETERMINED USING A DESIGN SPEED EQUAL TO THE POSTED SPEED AND A MAXIMUM SUPERELEVATION RATE OF 0.08, A MAXIMUM SUPERELEVATION RATE OF 0.06 WAS USED WHERE SIDE ROADS INTERSECTED ALONG THE HIGH SIDE OF A CURVE.
2. THE SHOULDER CROSS SLOPE ON BOTH THE OUTSIDE (HIGH SIDE) AND THE INSIDE (LOW SIDE) OF A SUPERELEVATED CURVE SHALL MATCH THE ADJACENT TRAVEL LANE CROSS SLOPE.



PROJECT NAME: ROCHESTER	FILE NAME: z13cl76sbd07.dgn	PLOT DATE: 1/11/2017
PROJECT NUMBER: ER STP 0162(21)	PROJECT LEADER: D. GOZALKOWSKI	DRAWN BY: J. HEALD
	DESIGNED BY: J. OLSEN	CHECKED BY: J. SHIELDS
	SUPERELEVATION DIAGRAMS SHEET #7	SHEET 131 OF 360