



MMU 516 Malfunction Management Unit

PROGRAMMING

- Minimum flash, 0-16 seconds
- Short yellow per channel
- Programmable sequence monitor
- Latch selectable options

INDICATIONS

- Conflict LED
- Red Fail LED
- 24 V-1
- 24 V-2
- Controller Voltage Monitor
- Red+Yel Clearance
- Clearance
- Diagnostics
- Port 1 Fault, Tx, Rx
- Program Card Ajar
- Indication Fail LED
- Field Check
- Power LED
- Type 12 Mode

ENVIRONMENTAL

- Operating Temperature: -34° C to +74° C
- Storage Temperature: -45° C to +85° C
- Humidity: Less than 95% non-condensing to +43° C

FEATURES

- Meets and exceeds TS2-1992 Specifications
- Operates in TS1 Cabinets
- EPROM Memory
- No batteries
- Machine tooled socket I.C.'s
- Programmable Minimum Flash Time
- Latch 24 V failures
- Latch CVM Failure
- Enhanced Monitoring

ELECTRICAL

• Power

Line Voltage: 75 to 150 VAC, RMS
Line Frequency: 57 to 63 Hz,
60Hz nominal
Power: 10 watts, typical
Fuse, Front Panel: 0.5A Slow Blow

• Monitoring Voltage

Pickup: 96 +/- 2.5 Volts AC, RMS
Dropout: 91 +/- 2.5 Volts AC, RMS
Hysteresis: 4 +/- 1.0 Volts AC, RMS

DIMENSIONS

- Height: 10.5 inches
- Width: 4.5 inches
- Depth: 10.9 inches

Your Naztec Representative:



Highway Tech Signal Equipment Sales, Inc.
8 Gardiner Road / P.O. Box 1209
Sabattus, ME 04280
Tel. (207) 375-8248
Fax (207) 375-8279

820 Park Two Drive Sugar Land, TX 77478 (281) 240-7233
www.naztec.com naztec@naztec.com Additional Offices in Florida and Virginia