

RUMBLE STRIP LOCATIONS

NOTE: PRIOR TO PLACEMENT OF RUMBLE STRIPS ALL LOCATION SHALL BE FIELD VERIFIED BY THE ENGINEER AND PROJECT MANAGER.

POWNAI US ROUTE 7	BENNINGTON US ROUTE 7
MM 0.080 - 0.246	MM 0.000 - 0.060
MM 0.344 - 0.459	MM 0.263 - 0.430
0.566 MM 0.548 - 1.674	MM 0.920 - 1.366 0.921 - 1.347
MM 1.961 - 2.163 2.144	MM 1.589 - 1.777
MM 2.360 - 4.558	MM 1.826 - 1.967
6.049 MM 6.031 - 6.677	
7.182 MM 7.164 - 7.670 7.510	
7.7359 MM 7.717 - 7.854	
MM 7.962 - 8.000	

NOTE:

SEE MILLED RUMBLE STRIP (CENTERLINE) DETAILS HSD-213.02. TWO APPLICATIONS OF FOG SEAL SURFACE TREATMENT SHALL BE APPLIED TO THE COMPLETED CENTERLINE RUMBLE STRIPS AT A RATE OF 0.15 GAL./SY. WITH A TOLERANCE OF +/- 0.05 GAL./SY. OR AS DIRECTED BY THE ENGINEER. THERE SHALL BE A 14 DAY CURE TIME FOR THE FOG SEAL SURFACE TREATMENT BEFORE ANY PAVEMENT MARKING CAN BE APPLIED.

PROJECT NAME: POWNAL-BENNINGTON
PROJECT NUMBER: NH RMBL(3)

FILE NAME: pl4v201Bennington-Wilmington.dg PLOT DATE: 28-MAR-2017
PROJECT LEADER: M. FOWLER DRAWN BY: N. PAPPAS
DESIGNED BY: N. PAPPAS CHECKED BY: M. FOWLER
PROJECT NOTES SHEET 8 OF 64