

ONLY TOMAR 209X-SD Detectors offer these important features:

- Military derived sensor technology for direct sunlight rejection and detection performance unmatched by ANY other system.
- Fully encapsulated electronics for complete resistance to water, heat, and vibration.
- Complete electronics protection from damage due to miswiring or electrical transients.
- Wide field of view option for uncompromised detection even in untethered span wire applications without the risk of side street activation.
- Simple parallel detector installation without any special cabling for enhanced detection around corners and over hills.

Specifications for 2090-SD and 2091-SD Detectors

Item	Description
Maximum Range	2500 feet minimum when used with a TOMAR 2000 Series Optical Signal Processor.
Optical Pulse Rise Time Discrimination	The 2090-SD and 2091-SD input stages are optimized for the detection of strobe pulses with a rise time from start of pulse to peak of pulse of 10 microseconds or less. Slower pulses such as varying sunlight and incandescent emergency lighting will be highly attenuated and substantially ignored by the detector's digital discriminators.
2090-SD Field of View	13 degrees conical centered about the viewport normal axis (typical).
2091-SD Field of View	60 degrees conical centered about the viewport normal axis (typical).
Power Requirements	VOLTAGE: 12 to 30VDC CURRENT: 15 mA maximum
Wiring Connections	Blue Wire - GROUND Yellow - SIGNAL Orange Wire - +12 to 30 VDC Shield and Drain Wire - CONNECT TO BLUE WIRE AT TRAFFIC CABINET
Temperature Range	-40° Celsius to +75° Celsius
Physical Construction	The 2090-SD and 2091-SD enclosures are black, glass-filled, UV stabilized, polycarbonate suitable for all-weather use. All electronic circuitry is completely encapsulated in polyurethane for protection from shock, vibration, and moisture. A weep hole is provided for allowing the escape of condensation or other internal moisture build-up in the sight tube of the detector.
Size and Weight	2.75" dia. (69.8 mm) X 3.375" tall (85.7 mm) with side mounted 4" long (101.5 mm) sight tube
Mounting	The 2090-SD and 2091-SD are easily mounted using standard hardware on either span wire or mast arm. The unit has a 1/2" female pipe mount hub and internal terminal block for connection to a 3/C shielded detector cable. ***** See catalog page 23 for available mounting hardware.

Available Option

Model No.	Description
2091-OPTIC	Upgrade package that allows the user to convert a 2090-SD detector in the field to a 2091-SD.
2090-OPTIC	Upgrade package that allows the user to convert a 2091-SD detector in the field to a 2090-SD

