| LOCATION | | | GUARDRAIL | | | | | | REMARKS |
|---|---|---|---|---|---|---|---|---|---|
| | | | 621.20 | 621.60 | 621.75 | 621.80 | 676.10 | 676.12 | |
| MM | MM | POS | STEEL BEAM GUARDRAIL GALV. | ANCHOR FOR STEEL BEAM RAIL | REMOVE AND RESET GUARDRAIL | REMOVAL & DISPOSAL OF GUARDRAIL | DELIN. W/STEEL POST | REMOVAL OF EXIST. DELIN. | |
| | | | LF | EACH | LF | LF | EACH | EACH | |
| 21+59.0 | N 112+48.0 | LT/RT | | | | | | 24 | ESTIMATED QUANTITY TO BE REMOVED AS DIRECTED BY THE ENGINEER |
| | | | | | | | | | |
| | ROXBURY | | | | | | | | |
| 77+03.0 | 77+40.5 | LT | | | | 37.5 | | | REMOVE MELT |
| 77+03.0 | 77+40.5 | LT | 39.5 | 1 | | | 1 | | SEE STANDARD G-1d |
| 77+40.5 | N 2+81.0 | LT | | | 337.5 | | | | |
| N 2+81.0 | N 3+31.0 | LT | | | | 50.0 | | | REMOVE MELT |
| N 2+81.0 | N 3+31.0 | LT | 52.0 | 1 | | | 1 | | SEE STANDARD G-1d |
| | | | | | | | | | |
| | NORTHFIELD | | | | | | | | |
| N 8+63.0 | N 9+00.5 | LT | | | | 37.5 | | | REMOVE MELT |
| N 8+63.0 | N 9+00.5 | LT | 39.5 | 1 | | | 1 | | SEE STANDARD G-1d |
| N 9+00.5 | N 12+93.0 | LT | | | | | 1 | | RETAIN GUARDRAIL |
| | | | | | | | | | |
| N 14+32.0 | N 14+69.5 | LT | | | | 37.5 | | | REMOVE MELT |
| N 14+32.0 | N 14+69.5 | LT | 39.5 | 1 | | | 1 | | SEE STANDARD G-1d |
| N 14+69.5 | N 14+94.5 | LT | | | 25.0 | | | | |
| N 14+94.5 | N 16+96.0 | LT | | | | | | | RETAIN GUARDRAIL |
| N 16+96.0 | N 17+21.0 | LT | | | 25.0 | | | | |
| N 17+21.0 | N 17+71.0 | LT | | | | 50.0 | | | REMOVE MELT |
| N 17+21.0 | N 17+71.0 | LT | 52.0 | 1 | | | 1 | | SEE STANDARD G-1d |
| | | | | | | | | | |
| N 27+00.0 | N 27+50.0 | LT | | | | 50.0 | | | REMOVE MELT |
| N 27+00.0 | N 27+50.0 | LT | 52.0 | 1 | | | 1 | | SEE STANDARD G-1d |
| N 27+50.0 | N 28+00.0 | LT | | | 50.0 | | | | |
| N 28+00.0 | N 34+39.5 | LT | | | | | | | RETAIN GUARDRAIL |
| N 34+39.5 | N 34+64.5 | LT | | | 25.0 | | | | |
| N 34+64.5 | N 35+02.0 | LT | | | | 37.5 | | | REMOVE MELT |
| N 34+64.5 | N 35+02.0 | LT | 39.5 | 1 | | | 1 | | SEE STANDARD G-1d |
| | | | | | | | | | |
| N 36+99.0 | N 37+49.0 | LT | | | | 50.0 | | | REMOVE MELT |
| N 36+99.0 | N 37+49.0 | LT | 52.0 | 1 | | | 1 | | SEE STANDARD G-1d |
| N 37+49.0 | N 38+21.5 | LT | | | | | | | RETAIN GUARDRAIL |
| N 38+21.5 | N 38+46.5 | LT | | | 25.0 | | | | |
| N 38+46.5 | N 38+84.0 | LT | | | | 37.5 | | | REMOVE MELT |
| N 38+46.5 | N 38+84.0 | LT | 39.5 | 1 | | | 1 | | SEE STANDARD G-1d |
| | | | | | | | | | |
| N 37+18.0 | N 37+55.5 | RT | | | | 37.5 | | | REMOVE MELT |
| N 37+18.0 | N 37+55.5 | RT | 39.5 | 1 | | | 1 | | SEE STANDARD G-1d |
| N 37+55.5 | N 44+94.5 | RT | | | | | | | RETAIN GUARDRAIL |
| N 44+94.5 | N 45+07.0 | RT | | | 12.5 | | 1 | | |
| | | | | | | | | | |
| N 45+34.0 | N 47+21.5 | RT | | | 187.5 | | 1 | | |
| N 47+21.5 | N 47+71.5 | RT | | | | | | | RETAIN GUARDRAIL |
| N 47+71.5 | N 47+96.5 | RT | 25.0 | | | 25.0 | | | |
| N 47+96.5 | N 63+46.5 | RT | | | | | | | RETAIN GUARDRAIL |
| N 63+46.5 | N 65+21.5 | RT | | | 175.0 | | | | |
| N 65+21.5 | N 70+75.0 | RT | | | | | | | RETAIN GUARDRAIL |
| N 70+75.0 | N 77+00.0 | RT | | | 625.0 | | 1 | | |
| | | | | | | | | | |
| N 75+71.0 | N 75+83.5 | LT | | 1 | 12.5 | | 1 | | NEW "W" BEAM END SECTION |
| N 75+83.5 | N 80+24.5 | LT | | | | | | | RETAIN GUARDRAIL |
| N 80+24.5 | N 80+37.0 | LT | | 1 | 12.5 | | 1 | | NEW "W" BEAM END SECTION |
| | | | | | | | | | |
| N 77+44.0 | N 78+41.0 | RT | | | 100.0 | | 2 | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | **SUBTOTAL SHEET 9** | | 470.0 | 12 | 1612.5 | 450.0 | 18 | 24 | |

PROJECT NAME: ROXBURY-NORTHFIELD
PROJECT NUMBER: STP FPAV(6)

FILE NAME: z16v027frm.dgn
PROJECT LEADER: P. SHEDD
DESIGNED BY: N. LEMAY
ITEM DETAIL SHEET I

PLOT DATE: 2/8/2017
DRAWN BY: S. GOODWIN
CHECKED BY: P. SHEDD
SHEET 9 OF 21