



BEGIN PAVEMENT MARKING
STA 103+50 20 AC

(R) (S)
RELOCATE TO
STA 104+00 LT
SPEED
LIMIT
50
N AB

(R) (S)
RELOCATE
STA 104+
SPEED
LIMIT
40
T

PAVEMENT MARKINGS - LINES

LOCATION	AB		AB		AB		AB	
	DURABLE 4" WHITE, SINGLE	TYPE	DURABLE 4" YELLOW, DOUBLE	DURABLE 4" YELLOW, SINGLE	DURABLE 4" WHITE, DASHED	DURABLE 4" WHITE, DOTTED	DURABLE 8" DIAG YELLOW	
ROUTE 5 AB								
U.S. RTE 5								
STA 103+50 TO 120+40 LT	1715	4660 LF						
STA 103+50 TO 120+30 RT	1701	4680 LF						
STA 103+50 TO 120+35 C			1702	4685 LF				
STA 121+20 TO 122+35 RT VCH 1950	443	120 LF						
STA 121+30 TO 122+40 LT VCH 1280	360	120 LF						
STA 121+30 TO 122+35 C	226	115	405 LF					
STA 122+35 RT		1815	2890					
SUBTOTAL	4085	3620 LF	1290	2	3680			
SERVICE DRIVE								
STA 0+15 LT								
STA 0+15 TO 0+30 C		37	85 LF					
STA 1+00 TO 3+00 C		98	201 LF					
SUBTOTAL		135	266	2	512	270		
U.S. RTE 5/VERMONT RTE 11								
STA 12+80 TO 14+10 (MEDIAN)		300	265 LF				168	
STA 12+80 TO 14+10 LT	198	120 LF			30 LF		320 LF	
STA 12+80 TO 14+10 RT					30 LF			
STA 12+90 TO 13+35 RT		45 LF						
STA 14+90 TO 16+25 RT			256	495 LF	70	26 LF		
STA 14+90 TO 18+55 LT			370	365 LF				
STA 14+45 TO 16+25 RT		190 LF						
STA 14+95 TO 18+55 LT		357	370 LF					
STA 14+90 TO 16+55 LT		165 LF						
STA 14+90 TO 18+55 LT					90 LF			
STA 16+55 TO 18+55 LT		300	600			80 LF	168	
SUBTOTAL	670	890 LF	295	2	80	23	486 LF	820 LF
TOTAL	4755	4580 LF	4500	4602 LF	626	500 LF	235	485 LF

LEGEND

- (R) REMOVE
- (N) NEW
- (S) SALVAGE

DATUM	NGVD 1929
VERTICAL	N/A
HORIZONTAL	N/A