



ANCHOR BOLT NOTE:
ALL ANCHOR BOLTS FOR BEARING DEVICES TO BE CAST IN PLACE DURING CONCRETE CAP POUR.

NOTES:

1. 3" CLEAR COVER IN FOOTING UNLESS OTHERWISE NOTED.
2. 4" CLEAR COVER ON ALL EXPOSED FACES IN STEM AND CAP.
3. E.F. - DENOTES EACH FACE.
4. ▲ - DENOTES CUT TO FIT IN FIELD.
5. | - DENOTES VERTICAL HP 12 X 74 PILE.
6. ▽ - DENOTES 1 ON 4 BATTERED HP 12 X 74 PILE.
7. △ - DENOTES CHANGES 11/96.
8. ▽ - DENOTES CHANGES 1/17/96.

STATE OF VERMONT AGENCY OF TRANSPORTATION	
Town Of SPRINGFIELD	Bridge No. 44
Highway No. U.S. ROUTE 5	Log Sta. Surv. Sta.
U.S. ROUTE 5 OVER BLACK RIVER	
PIER DETAILS	
Designed By S. BAKI	Drawn By W. GAYNOR / R. REMY
Checked By S. BAKI	Bridge Design Supervisor P. PIERCE
Date 7/95	Date 5/96
PROJECT SPRINGFIELD	PROJECT NO. BRS-RS 0113 (8)
I.G.C. Info. pl\9145622\struct\spiernew.dgn	
Bridge Sheet No. BRI27	Sheet 56R2 of 90