



BLOCKING DIAGRAM

LINES 1 THRU 7

NOTES

1. ALL HOLES SHALL BE SUBPUNCHED OR SUBDRILLED $\frac{11}{16}$ ϕ AND REAMED TO $\frac{1}{8}$ ϕ WITH ALL PARTS ASSEMBLED.
2. BLOCKING DIMENSIONS FOR SHOP ASSEMBLY ARE GIVEN TO THE BOTTOM OF WEB.
3. ALL LONGITUDINAL DIMENSIONS IN BLOCKING DIAGRAM ARE DEVELOPED ALONG THE ϕ OF GIRDER AT THE BASELINE.
4. ALL GIRDERS MUST BE ASSEMBLED AS PER DIAGRAM SHOWN PRIOR TO REAMING OR DRILLING. FOR FIELD SPLICE DETAILS SEE SHEET 10-1.

ITEM NO. 506.55	BR. NO. 44	PROJ. NO. BRS-RS 0113 (B)
TITLE: BLOCKING DIAGRAM		
APPROVED:		
PRINT DIST.		
S	12-14-96	APPR.
ORIG	12-3-96	FAB.
S	11-13-96	APP
ORIG	4-3-97	VAT
JOB: U.S. ROUTE 5 OVER BLACK RIVER SPRINGFIELD, VERMONT		
CUSTOMER: WINTERSETT, INC.		
DESIGNER: VERMONT AGENCY OF TRANSPORTATION		
CHECKED	10/96	(CSD)
DRAWN	9/96	CSD
WORK ORDER NO.	DRAWING NO.	REV.
15713	10-2	

